SCREENING SITE INSPECTION REPORT
FOR
FORD MOTOR CO OHIO TRUCK PLT (SIA)
AVON LAKE, OHIO
U.S. EPA ID: OHDO20626669

SS ID: NONE TDD: F05-9007-012 PAN: F0H0646SA

US EPA RECORDS CENTER REGION 5



955818

OCTOBER 18, 1991



ecology and environment, inc.

111 WEST JACKSON BLVD., CHICAGO, ILLINOIS 60604, TEL. 312-663-9415 International Specialists in the Environment

recycled paper

SIGNATURE PAGE
FOR
SCREENING SITE INSPECTION REPORT
FOR
FORD MOTOR CO OHIO TRUCK PLT (SIA)
AVON LAKE, OHIO
U.S. EPA ID: OHDO20626669
SS ID: NONE
TDD: F05-9007-012
PAN:F0H0646SA

Prepared by:

Santosh Sharma
FIT Team Leader
C.C. Johnson and Malhotra, P.C.

Reviewed by:

Sidney F. Paige
FIT Associate Project Manager
C.C. Johnson and Malhotra, P.C.

Approved by:

# TABLE OF CONTENTS

<u>Section</u>		Page
1	INTRODUCTION	1-1
2	SITE BACKGROUND	2-1
	2.1 INTRODUCTION	2-1
	2.2 SITE DESCRIPTION	2-1
	2.3 SITE HISTORY	2-1
3	SCREENING SITE INSPECTION PROCEDURES AND FIELD	
	OBSERVATIONS	3-1
	3.1 INTRODUCTION	3-1
	3.2 SITE REPRESENTATIVE INTERVIEW	3-1
	3.3 RECONNAISSANCE INSPECTION	3-2
	3.4 SAMPLING PROCEDURES	3-5
4	ANALYTICAL RESULTS	4-1
5	DISCUSSION OF MIGRATION PATHWAYS	5-1
	5.1 INTRODUCTION	5-1
	5.2 GROUNDWATER	5-1
	5.3 SURFACE WATER	5-3
	5.4 AIR	5-3
	5.5 FIRE AND EXPLOSION	5-4
	5.6 DIRECT CONTACT	5-4
6	REFERENCES	6-1

# Table of Contents (Cont.)

Appendix		Page
А	SITE 4-MILE RADIUS MAP	A-1
В	U.S. EPA FORM 2070-13	B-1
С	TANK CONTENTS AND CAPACITIES, FMC SITE	C-1
D	FIT SITE PHOTOGRAPHS	D-1
E	U.S. EPA TARGET COMPOUND LIST AND TARGET ANALYTE LIST QUANTITATION/DETECTION LIMITS	E-1
F	ON-SITE SOIL BORING LOGS	F-1
G	WELL LOGS OF THE AREA OF THE SITE	G-1

# LIST OF FIGURES

<u>Figure</u>		Page
2-1	Site Location	2-2
3-1	Site Features	3-3
3-2	Soil Sampling Locations	3-6

# LIST OF TABLES

	<u>Table</u>		<u>Page</u>
•	4-1	Results of Chemical Analysis of FIT-Collected Soil Samples	4-2
-			
•			
•			
•			
_			

#### 1. INTRODUCTION

Ecology and Environment, Inc. (E & E), Field Investigation Team (FIT) was tasked by the United States Environmental Protection Agency (U.S. EPA) to conduct a screening site inspection (SSI) of the Ford Motor Co Ohio Truck Plt (SIA) (FMC) site under contract number 68-01-7347. C.C. Johnson and Malhotra, P.C. (CCJM), a subcontractor to E & E under the above contract, was responsible for conducting this investigation.

The FMC site was initially discovered by U.S. EPA on August 18, 1980, when Ford Motor Company (Ford) filed a Notification of Hazardous Waste Activity form, pursuant to section 3001 of the Resource Conservation and Recovery Act (RCRA). The notification was filed on August 18, 1980. The site was subsequently evaluated in the form of a preliminary assessment (PA). The PA was prepared by Pam Wicks of the Ohio Environmental Protection Agency (OEPA) and is dated May 6, 1985 (U.S. EPA 1985).

FIT prepared an SSI work plan for the FMC site under technical directive document (TDD) F05-8706-280, issued on June 19, 1987. The SSI work plan was approved by U.S. EPA on June 21, 1990. The SSI of the FMC site was conducted on February 28, 1991, under TDD F05-9007-012 issued on August 2, 1990.

The FIT SSI included an interview with site representatives, a reconnaissance inspection of the site, collection of nine soil samples, and photographing current site conditions and sampling locations.

The purposes of an SSI have been stated by U.S. EPA in a directive outlining Pre-Remedial Program strategies. The directive states:

All sites will receive a screening SI to 1) collect additional data beyond the PA to enable a more refined preliminary HRS [Hazard Ranking System] score, 2) establish priorities among sites most likely to qualify for the NPL [National Priorities List], and 3) identify the most critical data requirements for the listing SI step. A screening SI will not have rigorous data quality objectives (DQOs). Based on the refined preliminary HRS score and other technical judgement factors, the site will then either be designated as NFRAP [no further remedial action planned], or carried forward as an NPL listing candidate. A listing SI will not automatically be done on these sites, however. First they will go through a management evaluation to determine whether they can be addressed by another authority such as RCRA [Resource Conservation and Recovery Act] .... Sites that are designated NFRAP or deferred to other statutes are not candidates for a listing SI.

The listing SI will address all the data requirements of the revised HRS using field screening and NPL level DQOs. It may also provide needed data in a format to support remedial investigation work plan development. Only sites that appear to score high enough for listing and that have not been deferred to another authority will receive a listing SI. (U.S. EPA 1988)

U.S. EPA Region V has also instructed FIT to identify sites during the SSI that may require removal action to remediate an immediate human health or environmental threat.

# 2. SITE BACKGROUND

### 2.1 INTRODUCTION

This section presents information obtained during the SSI work plan preparation, the site representative interview, and the reconnaissance inspection of the site.

## 2.2 SITE DESCRIPTION

The FMC site is a 412-acre active truck assembly and painting facility. The site is located at 650 Miller Road, Avon Lake, Lorain County, Ohio (T.7N., R.16W.) (see Figure 2-1 for site location). The site is located approximately 9/10 miles south of Lake Erie. Land in the area of the site is used for commercial, industrial, residential, and agricultural purposes.


A 4-mile radius map of the FMC site is provided in Appendix A.

## 2.3 SITE HISTORY

Ford has operated truck assembly and painting operations on-site since 1975. The site was owned and operated by Fruehauf Corporation from 1946 to 1975. Fruehauf Corporation manufactured semitrailer bodies at the site (Molnar, Straub, and Waskiewicz 1991). The type and quantity of wastes generated during this period are not known.

Ownership and operation at the FMC site prior to 1946 is not known.

In 1975, Ford purchased the site from Fruehauf Corporation and began its truck assembly and painting operations. Ford used the existing buildings and also constructed more as part of a plant expansion program (Molnar, Straub, and Waskiewicz 1991).



SOURCE: USGS, Avon, OH Quadrangle, 7.5 Minute Series, 1963. Photorevised 1979.




FIGURE 2~1 SITE LOCATION

On-site operations include electroplating, assembling, and painting van bodies (Molnar 1991). Raw materials used for current operations on-site include steel, paints, solvents, sealers, naphtha blends, ferric chloride, sulfuric acid, sodium hydroxide, sodium bisulfite, and nitric acid (Molnar 1991; Molnar, Straub, and Waskiewicz 1991).

Hazardous waste generated on-site includes wastewater treatment sludges from industrial painting (F018), paint residues from industrial painting (F017 and D002), spent non-halogenated solvents (F001, F003, and F005), and waste commercial chemical products (xylene [U239] and toluene [U22] (Ford 1981; Molnar, Straub, and Waskiewicz 1991).

In 1990 the waste generated from various assembly and painting activities on-site included 760,125 pounds of liquid waste purge solvents (containing xylene methyl isobutyl ketone [MIK]), 1,238,472 pounds of waste paints and solvents (containing MIK), 62,000 pounds of ignitable liquid waste sealer solvent sludge (containing xylene and toluene), 9,900 pounds of oily sludge (containing xylene and MIK), 12,860 pounds of E-Coat sludge (containing lead), and 36,000 pounds of waste automotive sealer (containing lead) (Molnar 1991). FIT file information does not indicate the quantities of hazardous waste generated in previous years.

Two on-site cement-lined lagoons were used for the treatment and storage of wastes generated by the electroplating operations on-site. These lagoons were closed in 1985 and 1986. The sludge was removed from the lagoons, the concrete was broken, and the lagoons were filled with soil. The lagoon area is currently paved. Plant buildings and a wastewater treatment plant (WWTP) are located above the former lagoons (Molnar, Straub, and Waskiewicz 1991).

A stormwater pond was located in the northeast corner of the site. The pond was closed in 1985 (Molnar, Straub, and Waskiewicz 1991). That area is now covered with grass. Runoff water from the site is currently collected in a pond located on the west side of the site.

Waste purge solvents are recycled at an off-site location. Waste paints and solvents are blended off-site for a fuels program. The E-Coat sludge and waste automotive sealer are shipped off-site for treatment and disposal. Waste sealer solvent sludge and oily sludge are transported off-site to a disposal facility (Molnar 1991; Molnar,

Straub, Waskiewicz 1991). The waste generated is stored in two on-site underground storage tanks or in 55-gallon drums, and then shipped off-site for treatment and/or disposal (Molnar, Straub, Waskiewicz 1991). Drury Brothers, Petro-Chem Processing, Chem Freight, Automn Industries, Nave, Inc., and Nortru, Inc., are the listed transporters of the hazardous waste generated on-site (Molnar 1991).

Wastewater from the WWTP is discharged into Avon Lake sanitary sewer system. Discharge from the WWTP is regulated by a permit issued by the City of Avon Lake. The permit regulates pH, cadmium, chromium, zinc, nickel, copper, lead, and cyanide levels in the discharged wastewater. The discharged wastewater was sampled on several occasions. Analysis of samples detected cadmium, chromium, copper, lead, nickel, zinc, and cyanide above allowable limits (Sanford 1985). The permit (number MF-101) is effective from March 1, 1989, to March 1, 1994 (Molnar 1991).

Three spills occurred on-site in 1979. On April 24, 1979, 30 gallons of hydraulic fluid spilled from a 55-gallon drum. Approximately 10 gallons of the fluid was recovered by spill control measures. The rest drained into an underground storm sewer and was discharged into Lake Erie (Merta 1979a). The second spill occurred on July 13, 1979, when 200 gallons of E-Coat resin overflowed from a tank while the tank was being filled by a supplier. Approximately 10 gallons of resin entered the sewer system and the remainder was recovered (Merta 1979). The third spill occurred on August 9, 1979, when an unknown amount of petroleum naphtha overflowed from a tank while the tank was being filled by a supplier (Merta 1979b). Ford did try to clean up the spill, but the exact method of cleanup is not known. Ford notified OEPA about each of the spills. After these spills occurred, Ford developed a pollutant spill prevention plan for the site, and no further spills have been reported (U.S. EPA 1985).

On April 6, 1981, Ford applied for a RCRA permit for the site. OEPA granted the permit. However, Ford requested a withdrawal of the permit on July 20, 1981, after U.S. EPA deleted hazardous waste number F018 (wastewater treatment sludge from industrial painting) from its list of hazardous wastes (Merta 1981). The permit withdrawal was

granted, and since then OEPA has been conducting regular inspections of the site for compliance with U.S. EPA RCRA hazardous waste regulations (U.S. EPA 1985).

On February 10, 1982, Helen Takacs of OEPA, Division of Hazardous Material Management, conducted an inspection of the site. During this inspection, it was found that operations at the FMC site met the criteria for the site to be considered a RCRA hazardous waste generator. Operations at the site were in compliance with State of Ohio hazardous waste regulations, with the exception that some required information was not included in the site contingency plan (Takacs 1982).

On April 25, 1985, an inspection was conducted by Mark Bergman of OEPA, for compliance with state and federal regulations for the handling of hazardous wastes. The operation of the storage lagoons was found to be in violation of generator, and treatment, storage, and disposal of hazardous waste regulations. The exact nature of the violations is not known (Bergman 1985).

On-site operations were found to be in violation of electroplating wastewater pretreatment standards on five different occasions between August 19, 1984, and March 23, 1985. These violations pertain to the presence of nickel, zinc, and total metals detected above allowable limits in the wastewater treatment plant discharge (Kausek 1985; Sanford 1985; and Wiacek 1985).

No other regulatory or remedial response activities have been undertaken at the FMC site (Molnar, Straub, and Waskiewicz 1991).

## SCREENING SITE INSPECTION PROCEDURES AND FIELD OBSERVATIONS

## 3.1 INTRODUCTION

This section outlines procedures and observations of the SSI of the FMC site. Individual subsections address the site representative interview, reconnaissance inspection, and sampling procedures. Rationales for specific FIT activities are also provided. The SSI was conducted in accordance with the U.S. EPA-approved work plan with the following exceptions. A total of nine soil samples were collected instead of six soil samples and two sediment samples, as proposed in the work plan. Two sediment samples were not collected from the former stormwater pond because the pond was closed and the area was filled. FIT could not collect sediment samples from the current stormwater pond because the pond was too deep and inaccessible. Instead of the two potential background soil samples proposed in the work plan, only one potential background soil sample was collected. FIT considered one background sample to be adequate to characterize wastes present on-site.

The U.S. EPA Potential Hazardous Waste Site Inspection Report (Form 2070-13) for the FMC site is provided in Appendix B.

## 3.2 SITE REPRESENTATIVE INTERVIEW

Nahid Brown, Mathew Joseph, and Charles Onyezia of CCJM conducted an interview with Anne B. Molnar, Plant Engineer, Ford; Ron Straub, Plant Manager, Ford; and Kathy Waskiewicz, Environmental Engineer, Principal Facility, Ford, Dearborn, Michigan, on February 28, 1991. The interview was conducted in a conference room at the FMC site. The interview began at 9:00 a.m. The interview was conducted to gather information that would aid FIT in conducting SSI activities.

# 3.3 RECONNAISSANCE INSPECTION

Following the site representative interview, FIT conducted a reconnaissance inspection of the FMC site and surrounding area in accordance with E & E health and safety guidelines (E & E 1987). The reconnaissance inspection began at 10:30 a.m. on February 28, 1991, and included a walk-through of the site to determine appropriate health and safety requirements for conducting on-site activities and to make observations to aid in characterizing the site. FIT also determined sampling locations during the reconnaissance inspection. FIT was accompanied by Molnar and Waskiewicz during the reconnaissance inspection.

Reconnaissance Inspection Observations. The FMC site is located in Avon Lake, Ohio, approximately 9/10 miles south of Lake Erie. Walker Road forms the northern boundary of the site, Abbe Road forms the western boundary of the site, Norfolk and Western Railroad tracks form the southern boundary of the site, and Miller Road forms the eastern boundary of the site. The site is surrounded by a fence. The main entrance to the site is from Abbe Road on the west (see Figure 3-1 for site features). A paved road runs through the site, from the main entrance to an emergency gate on the east side of the site. Three more entrance gates are located on the west side of the site, and one on the north side of the site. There is a security guard at the main entrance gate at all times (Molnar, Straub, and Waskiewicz 1991).

The paved road leads east, toward the body shop, paint shop, the WWTP, and other on-site facilities. The body shop and paint shop share a large building that covers much of the east and central portions of the area north of the paved road. The paint shop occupies the west wing of the building, and the body shop occupies the east wing of the building. A power house is located approximately 50 yards north of the southwest corner of the body shop. There are two "set down" areas located south of the body shop and one located north of it. These are used for temporary storage of trucks and van parts until used in production (Molnar, Straub, and Waskiewicz 1991). The area between




FIGURE 3-1 SITE FEATURES

Miller Road and the east side of the body shop is the location of the resin spill that occurred in 1979. This area is now covered with gravel and asphalt. A former stormwater pond was located in the northeast corner of the site. This pond was closed in 1986 (Molnar, Straub, and Waskiewicz 1991) and now the area is covered with grass.

The paint shop is located west of the body shop. A paint sludge building is located west of the paint shop. This building is used for storing drums containing waste paint sludge. At the south end of the paint shop is a paint kitchen where paints and raw materials are mixed before use. West of the paint kitchen are wooden racks. Drums are placed on the racks before loading onto trucks for shipment to off-site locations. South of these wooden racks is the loading dock area. On the east side of the paint kitchen are two 12,000-gallon underground storage tanks (USTs). One of these is used for storing purged solvent, while the other is used for storing waste paints. Another UST is located north of the the paint shop. This UST stores diesel fuel (Molnar, Straub, and Waskiewicz 1991) (see Appendix C for tank contents and capacities at the FMC site).

North of the body shop and paint shop is the former lagoon area, which is now the location of the WWTP (Molnar, Straub, and Waskiewicz 1991). The area is currently covered with an asphalt drive, buildings, and the WWTP.

North of the entrance gate, on the west side of the site, is a stormwater pond where surface water runoff from the site is collected. A parking lot is located between the stormwater pond and the paint sludge building. The area between the stormwater pond and the parking lot is covered with grass.

Most of the area south of the paved road is covered by three asphalt-covered parking lots. A number of aboveground storage tanks, used for storing raw materials, are located on-site. These include four propane tanks located south of the emergency gate, near the setdown areas.

FIT photographs from SSI of the FMC site are provided in Appendix D.  $\,$ 

### 3.4 SAMPLING PROCEDURES

Samples were collected by FIT at locations selected during the reconnaissance inspection to determine whether U.S. EPA Target Compound List (TCL) compounds or Target Analyte List (TAL) analytes were present at the site. The TCL and TAL are included with corresponding quantitation/detection limits in Appendix E.

On February 28, 1991, FIT collected nine on-site soil samples, including a potential background sample. Site representatives were offered a portion of the on-site samples, and the offer was accepted.

Soil Sampling Procedures. Soil sample S1 was collected at a depth of 3 feet from a location in the northeast corner of the FMC site (see Figure 3-2 for soil sampling locations). Sample S1 was collected from the southeast edge of the former stormwater pond area. The sample consisted of firm dark brown clay. Surface soil sample S2 was collected at a depth of 2 to 6 inches, from an area near the loading dock, south of the paint shop. The sample was collected in an area where drums of waste materials are loaded onto trucks for shipment to off-site locations. The sample consisted of light brown clay. Surface soil sample S3 was collected approximately 50 feet west of sampling location S2, near the drum storage area. Sample S3 was collected at a depth of 2 to 6 inches. The sample consisted of brown clay. Surface soil sample S4 was collected at a depth of 2 to 6 inches from a location between the power house and the body shop, in an area where the vegetation appeared to be different from the other on-site areas. The sample was brown and consisted of clay. Soil sample S5 was collected at a depth of 2 1/2 feet from a location in the area of the two former lagoons, north of the WWTP. The sample consisted of dry clay. Surface soil sample S6 was collected adjacent to the southeast corner of the former stormwater pond. The sample was collected at a depth of 2 to 6 inches, from a location near a construction pile. The sample consisted of clay loam with pebbles. Surface soil sample S7 was collected from the southeast portion of the former lagoon area. The sample was collected at a depth of 2 to 6 inches, and consisted of clay. Surface soil sample S9 was collected at a depth of 2 to 6 inches, from a location east of the stormwater detention pond. The sample consisted of saturated clay with pebbles, gravel, and rootlets.




FIGURE 3-2 SOIL SAMPLING LOCATIONS

Surface soil sample S8 was collected as a potential background sample, from a location northwest of the paint shop. This area was purchased by Ford in 1988 and has not been used at anytime (Molnar, Straub, and Waskiewicz 1991). This sample was collected to assess the representative chemical composition of the soil in the area of the FMC site. The sample consisted of brown clay. Soil samples S1 and S5 were subsurface samples, collected using a hand auger. Soil samples S2 through S4 and S6 through S9 were surface samples, collected using a garden trowel.

The sample portions collected for volatile organic analysis were transferred directly to sample bottles. The remaining sample portions were placed into a stainless steel bowl, mixed, and then transferred to the appropriate sample bottles, using a stainless steel spoon (E & E 1987).

Standard E & E decontamination procedures were followed during the collection of all soil samples. The procedures included the cleaning of all equipment (e.g. trowels, hand auger, stainless steel bowl, and stainless steel spoons) with a solution of detergent (Alconox) and distilled water and triple-rinsing with distilled water before the collection of each sample (E & E 1987). All soil samples were packaged and shipped in accordance with U.S. EPA-required procedures.

As directed by U.S. EPA, all soil samples were analyzed using the U.S. EPA Contract Laboratory Program (CLP).

# 4. ANALYTICAL RESULTS

This section presents results of the chemical analysis of samples collected by FIT during the SSI of the FMC site. All samples were analyzed for volatile organics, semivolatile organics, pesticides/polychlorinated biphenyls (PCBs), metals, and cyanide. Complete chemical analysis results of FIT-collected soil samples are provided in Table 4-1.

Quantitation/detection limits used in the analysis of FIT-collected samples are provided in Appendix E.

The analytical data from the chemical analysis of FIT-collected samples for this SSI have been reviewed under the direction of U.S. EPA for validity; the review has been approved by U.S. EPA. The analytical data have also been reviewed by FIT for usability. Any additions, deletions, or changes resulting from review of the data have been incorporated in the chemical analysis results tables presented in this section.

Table 4-1
RESULTS OF CHEMICAL ANALYSIS OF
FIT-COLLECTED SOIL SAMPLES
FOR THE FMC SITE SSI

Sample Collection Information and Parameters	<b>S1</b>	25	<b>S3</b>	<b>S4</b>	<b>S</b> 5	<b>S6</b>	<b>S7</b>	\$8	29
Date	02/28/91	02/28/91	02/28/91	02/28/91	02/28/91	02/28/91	02/28/91	02/28/91	02/28/91
Time	1210	1230	1230	1310	1415	1445	1450	1505	1530
LP Organic Traffic Report Number	EMW72	EMW73	EMW74	EMW75	EMW76	emw77	EMW78	EMW79	EMM80
IP Inorganic Traffic Report Number	MEMW58	MEMW59	MEMW60 	MEMW61 	MEMW62 	MEMW63	MEMW64 	MEMW65 	MEMW66
Compound Detected									
(values in ug/kg)									
Volatile Organics				0.1	25 J		11 J	12 J	9 J
methylene chloride	100.3			9 J	25 J		11 0	12 0	_
acetone	130 J	12 J							14 J
carbon disulfide	2 J		2 J		1 J				
thloroform		_	2 0			_			
1,1,1-trichloroethane		2 J							
penzene	2 J	15 J			7 J			4 J	
toluene	3 J	15 0			<i>7</i> 0			26 J	
ethylbenzene		_			12 J			200	
xylenes (total)		_			12.0				
Semivolatile Organics					120 1				
2-methylnaphthal <b>ene</b>				- 1	130 J 92 J	130 J	250 J		
phenanthrene				230 J		200 J	550 J		
Fluoranthene			-	550 J 440 J	400 J 310 J	200 J	470 J		_
pyrene		-		260 J	140 J	100 0	260 J		
penzo[a]anthracene				290 J	140 J		330 J		
chrysene		_		290 J 210 J	110 J		240 J	_	89 J
penzo[b]fluoranthene				210 J 340 J	120 J	_	230 J		100 J
penzo[k]fluoranthene		_		240 J	91 J		200 J		
penzo[a]pyrene		_		240 J 160 J			110 J		
indeno[1,2,3-cd]pyrene			_	160 J	-		100 J		
penzo[g,h,i]perylene		-		1/0 0	<del></del>	<del></del>	100 0		
Pesticides/PCBs			1201						8.4 J
1,4'-00E			1303				_		25 J
1,4'-000	-	-	590						ں ت

<sup>· -</sup> Not detected.

Table 4-1 (Cont.)

Sample Collection Information and Parameters	<b>S1</b>	\$2	33	S4 	<b>S</b> 5	<b>56</b>	57	<b>38</b>	23
Analyte Detected									
(values in mg/kg)		10.400	00.000	en 000	10 200	04 000	17.600	10 900	30 EM
aluminum	24,300	19,400	26,800	21,900	18,300	24,200	17,600 R	19,800	20,500 R
antimony	R	9.7 BNJ	R	R	R	13.6 BNJ		R	9.1Ns*J
arsenic	7.8 NYJ	7.9 N*J	7.6 Ns*J	31.1 N*J	10.7 Ns*J	11.1 Ns*J	9.1 N*J	11.4 N*J	116
barium	174	125	132	124	76.5	167	94.9	97.3	
beryllium	2.3	0.98 B	1.4	1.1 B	1.5	2.3	1.7	1.4	1.4
cadmium	1.3				0.95 B			 5 410 41	
zalcium	50,800 ∜	51 <b>,80</b> 0 *V	6,460 N	11,800 *J	18,100*J	67,600 *J	20,700 *J	5,410 <sup>*</sup> U	25,700 *J
thromium	32.0	28.3	29.5	33.4	32.6	34.4	25.4	28.2	28.5
pobalt	13.2	12.7	7.8 B	12.1	11.4 B	12.4 B	15.2	12.3 B	10.3 B
copper	41.4	28.5	26.4	26.5	31.1	27.0	23.3	27.3	22.1
iron	36,900	29,600	22,500	31,300	29,400	29,300	45,400	34,000	28,600
lead	11.4 *	21.3 s*J	23.6 s∜J	29 <b>.</b> 2 <b>*</b> J	11.0 s∜J	33.7 <b>*</b> J	15.0 *J	17.7 *J	25.8 s∜J
nagnesium	10,700	17,100	4,200	8,660	6,190	14,600	7,220	5,400	5,570
manganese	1,700 N*J	418 N*J	189 <b>N*J</b>	389 N*J	569 N*J	2,830 N*J	755 N*J	279 N*J	416 N*J
nickel	34.3	37.0	29.2	53.5	39.7	33.0	33.7	42.1	26.8
ootassium	3,880 *	5,730 *	3,320 *	3,910 *	4,660 *	3,980 *	3,490 *	3,610 *	3,790 *
selenium	1.7 NsJ	_		-	3.9 NsJ	1.9 NsJ	_		
sodium	385 B	396 B	198 B	203 B	226 B	454 B	202 B	_	
challium	_	_			1.5 B		_		
vanadium	56.8 *	50.6 *	49.0 *	47.9 *	113 *	50.5 *	48.0 *	46.4 *	39.6 *
zinc	233	74.5	62.1	122	107	95.6	98.9	104	94.1

 Not	detected.

Indicates an estimated value.

#### ANALYTE QUALIFIERS

#### DEFINITION

# S N

J

J R

Analysis by Method of Standard Additions. Spike recoveries outside QC protocols, which indicates a possible matrix problem. Data may be biased high or low. See spike results and laboratory narrative. Duplicate value outside QC protocols which indicates a possible matrix problem.

DEFINITION

Value is real, but is above instrument DL and below CRDL.

Value is above CROL and is an estimated value because of a QC protocol.

Results are unusable due to a major violation of QC protocols.

#### INTERPRETATION

Compound value may be semiquantitative.

#### INTERPRETATION

Value is quantitative. Value may be quantitative or semiquantitative.

Value may be quantitative or semiquantitative.

Value may be quantitative or semiquantitative. Value may be semiquantitative.

Analyte value is not usable.

# 5. DISCUSSION OF MIGRATION PATHWAYS

#### 5.1 INTRODUCTION

This section presents discussions of data and information pertaining to potential migration pathways and targets of TCL compounds and TAL analytes that are possibly attributable to the FMC site.

The five migration pathways of concern discussed are groundwater, surface water, air, fire and explosion, and direct contact.

#### 5.2 GROUNDWATER

In accordance with the U.S. EPA-approved work plan, no groundwater samples were collected by FIT.

TCL compounds and TAL analytes were detected in on-site soil samples at levels above background, including acetone (130J ug/kg in S1), 4,4'-DDD (59 ug/kg in S3), 4,4'-DDE (130 ug/kg in S3), xylene (12J ug/kg in S5), antimony (13.6BNJ mg/kg in S6), manganese (2,830N\*J mg/kg in S6), and selenium (3.9NsJ mg/kg in S5) (see Table 4-1 for definition and interpretation of qualifiers). Acetone is a common chemical constituent of the solvents used in painting, and xylene is a waste generated on-site (Molnar 1991). Therefore presence of these compounds in the soil samples can be attributable to the on-site activities.

There is a potential for TCL compounds and TAL analytes to migrate from the FMC site to groundwater in the vicinity of the site, based on the following information.

- o TCL compounds and TAL analytes were detected at levels above background in on-site soil samples.
- o There is no engineered liner or containment system for the stormwater pond (Molnar 1991).

The potential for TCL compounds and TAL analytes to migrate from the site to groundwater is also based on the geology of the area of the site. The geology of the area consists of Wisconsinan lacustrine deposits overlying Devonian bedrock. These deposits consist of commonly laminated silt and clay, covered by marl and peat at certain locations, and underlain by till (Ohio Department of Natural Resources [ODNR] 1961).

Based on area well logs, the surface soil consists of 5 to 10 inches of silty clay loam (see Appendix F for on-site soil boring logs). Stiff brown and gray clay, along with some sand and silt and traces of gravel, are present beneath the surface soil. This layer is 5 to 6 feet thick. This layer is underlain by a 2- to 5-foot thick layer of very stiff brown and gray silt with some clay and traces of sand and gravel. Beneath this layer lies bedrock that consists of a weathered black and gray shale formation at a depth of 13 to 15 feet, containing water at varying depths. This formation is of Devonian age, and Oletangy and Ohio type (ODNR 1981).

Area well logs indicate that private wells in the area of the site draw water from the lacustrine deposits and from the bedrock. Well logs do not indicate that continuous confining layer exists within a 3-mile radius of the site. There, the lacustrine deposits and the bedrock are considered to be hydraulically connected and together form a single aquifer of concern (AOC). The depth to the AOC is 20 feet (see Appendix G for well logs of the area of the site). Based on area topography, the direction of groundwater flow is presumed to be toward the north.

Approximately 17 residential wells are located within a 3-mile radius of the site (Jones 1990). These wells are primarily used for watering lawns and gardens. These wells typically yield water at rates of 1 to 3 gallons per minute. Because of the low yield of the wells and the presence of high amounts of sulphur compounds in the water, people do not depend on groundwater as a source of drinking water in this area (Rodriguez 1991). The Avon Lake Water Department (ALWD), the Lorain Water Department (LWD), and the Rural Lorain County Water Authority (RLCWA) supply drinking water to the area. LWD and ALWD draw water from surface water intakes located in Lake Erie.

# 5.3 SURFACE WATER

In accordance with the U.S. EPA-approved work plan, no surface water samples were collected during the SSI of the FMC site. There is no potential for TCL compounds or TAL analytes to migrate from the site via surface water runoff, based on the following information.

- o The site is surrounded by railroad tracks and streets, which act as barriers to the migration of surface water.
- o Lake Erie, the body of surface water nearest to the site, is located approximately 9/10 miles from the site, and is separated from the site by roads and city streets.

However, there is a potential for TCL compounds and TAL analytes to migrate to Lake Erie via an underground storm sewer system. Lake Erie is used as a source of drinking water by ALWD (Knieper 1990). The surface water intake for this system is approximate 1 2/10 miles north of the site. ALWD supplies water to approximately 80,000 persons living in Avon Lake and nearby areas. The city of Sheffield Lake, which is located within a 3-mile radius of the site, obtains part of its water supply from ALWD and part from LWD. The surface water intake for the LWD system is located approximately 5 miles from the site. RLCWA supplies water to the site and surrounding area (RLCWA 1983). RLCWA purchases its water from ALWD and LWD. RLCWA serves a population of 13,000 persons (Jody 1991). Thus, the potential surface water target population for the FMC site is approximately 93,000 persons.

Lake Erie is used for recreational purposes. The Black River is located approximately 2 7/10 miles southwest of the site. There is no potential for TCL compounds and TAL analytes to migrate toward the Black River because the topography in the area of the site slopes northward. There are no wetlands or federally designated endangered species habitats within a 1-mile radius of the site.

#### 5.4 AIR

A release of TCL compounds or TAL analytes to the air was not documented during the SSI of the FMC site. During the reconnaissance inspection, FIT site entry equipment (organic vapor analyzer, explosimeter, colorimeteric monitoring tubes for hydrogen cyanide) did not detect levels that deviated from background levels at the site

(E & E 1987). In accordance with the U.S. EPA-approved work plan, further air monitoring was not conducted by FIT.

A potential does not exist for TCL compounds and TAL analytes to migrate from the site via windblown particulates because all areas of the site are paved or covered with grass.

#### 5.5 FIRE AND EXPLOSION

According to FIT observations and site-entry equipment readings, no apparent potential for fire or explosion existed at the FMC site at the time of the SSI. There is no record of an incident of fire or explosion at the site (Molnar, Straub, and Waskiewicz 1991). Numerous attempts to obtain information regarding fires and/or explosions at the FMC site were unsuccessful.

## 5.6 DIRECT CONTACT

According to federal, state, and local file information reviewed by FIT, observations made during the SSI, and the interview with site representatives, no incidents of direct contact with TCL compounds or TAL analytes at the FMC site have been documented (Molnar, Straub, and Waskiewicz 1991). There is no possibility for area residents to come into direct contact with TCL compounds and TAL analytes present at the site because the site is fenced on all sides and a guard is present at the main entrance at all times. However, there is a potential that the on-site workers may come into direct contact with TCL compounds or TAL analytes at the site because TCL compounds and TAL analytes were detected at levels above background in on-site surface soil samples. Approximately 1,900 persons work on-site (Molnar, Straub, and Waskiewicz 1991).

## REFERENCES

- Bergman, Mark, April 25, 1985, Environmental Scientist, Division of Solid and Hazardous Waste Management, OEPA, letter, to Tom Dunning, Ford, Avon Lake, Ohio, Re: site inspection on March 27, 1985.
- E & E, 1987, Quality Assurance Project Plan Region V FIT Conducted Site Inspections, Chicago, Illinois.
- Ford, November 1981, Hazardous Waste Supplement Amendment to Spill Prevention and Control and Countermeasure Plan.
- Jody, July 26, 1991, receptionist, RLCWA, Lagrange, Ohio, telephone conversation, contacted by Santosh Sharma of CCJM.
- Jones, Wayne, March 7, 1990, Hydrogeologist, Groundwater Division, ODNR, telephone conversation, contacted by Nahid Brown of CCJM.
- Kausek, Sandra, February 25, 1985, Environmental Scientist, Pretreatment Unit, OEPA, Twinsburg, Ohio, letter, to Matt Tim, Ford, Avon Lake, Ohio.
- Knieper, John W., January 24, 1990, Director, ALWD, Avon Lake, Ohio, telephone conversation, contacted by Mike Duet of CCJM.
- Merta, F. J., July 25, 1979, Plant Manager, Ford, Avon Lake, Ohio, letter, to Kenneth A. Shultz, OEPA, Twinsburg, Ohio, Re: E-coat resin spill on July 13, 1979.

- Merta, F. J., September 24, 1979a, Plant Manager, Ford, Avon Lake, Ohio, letter, to Kenneth A. Shultz, OEPA, Twinsburg, Ohio, Re: oil spill on April 24, 1979.
- Merta, F. J., September 26, 1979b, Plant Manager, Ford, Avon Lake, Ohio, letter, to Kenneth A. Shultz, OEPA, Twinsburg, Ohio, Re: naphtha spill on August 9, 1979.
- Merta, F. J., July 22, 1981, Plant Manager, Ford, Avon Lake, Ohio, letter, to Wayne S. Nichols, OEPA, Twinsburg, Ohio, Re: withdrawal of hazardous waste permit application.
- Molnar, Anne, May 3, 1991, Plant Engineer, Ford, Avon Lake, Ohio, letter, to Nahid Brown of CCJM.
- Molnar, Anne, B., Ron Straub, and Kathy Waskiewicz, February 28, 1991, Plant Engineer, Ford; Plant Manager, Ford; Environmental Engineer, Ford, Principal Plant, Dearborn, Michigan, respectively, interview, conducted by Nahid Brown, Mathew Joseph, and Charles Onyezia of CCJM.
- ODNR, 1961, Glacial Map of Ohio, prepared by Richard P. Goldthwait, George W. White, and Janes L. Forsyth.
- ----, 1981, <u>Geologic Map of Ohio</u>, prepared by J.A. Bownocker, Division of Geologic Survey, Columbus, Ohio.
- Rodriguez, Angel R., June 9, 1991, Director of Environmental Health, Lorain Health Department, telephone conversation, contacted by Santosh Sharma of CCJM.
- RLCWA, March 1983, Water Supply Map, Lorain County, Ohio.
- Sanford, J. H., January 15, 1985, Works Manager, Ford, Avon Lake, Ohio, letter, to M. B. Tin, Pretreatment Unit, OEPA, Twinsburg, Ohio, Resemi-annual pretreatment report.

- Takacs, Helen, February 24, 1982, Environmental Scientist, Division of Hazardous Material Management, OEPA, letter, to Jim Davis, Ford, Avon Lake, Ohio, Re: site inspection on February 10, 1982.
- U.S. EPA, May 6, 1985, <u>Potential Hazardous Waste Site Preliminary</u>
  <u>Assessment</u>, for the FMC site, U.S. EPA ID: OHDO20626669, prepared by Pam Wicks, Division of Solid Hazardous Waste Management, OEPA.
- Response, <u>Pre-Remedial Strategy for Implementing SARA</u>, Directive number 9345.2-01, Washington, D.C.
- Wiacek, J. J., July 19, 1985, Works Manager, Ford, Avon Lake, Ohio, letter, to M. B. Tin, Pretreatment Unit, OEPA, Twinsburg, Ohio, Resemi-annual pretreatment report.

APPENDIX A

SITE 4-MILE RADIUS MAP

APPENDIX B

U.S. EPA FORM 2070-13

# 7 SEPA

EPA FORM 2070-13 (7-81)

# POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 1 - SITE LOCATION AND INSPECTION INFORMATION

L IDENTIFICATION

01 STATE 02 SITE MUMBER

OHD 02 062 6669

II. SITE NAME AND LOCATION						
OT SITE NAME A POM. CONTROL OF PROCEDURA	_		Ĭ.		PECIFIC LOCATION IDENTIFIER	ŧ.
FORD MOTOR CO	OHIO TRUCK	: PLT (SIA)		650 MILLE	· · · · · · · · · · · · · · · · · · ·	
A VON LAKE			O4 STATI	44012	LORAIN	0700UNTY 08 CON 000E 05T 093 /3
09 COORDNATES 4 1° 2 4' 15" N 8 2°	LONGITUDE " N O 3' 4 5" N	10 TYPE OF OWNERSH 10 A. PRIVATE 11 F. OTHER			D C. STATE D D. COUNT	TY DE. MUNICIPAL
III. INSPECTION INFORMATION	1				-	
•	02 SITE STATUS	03 YEARS OF OPERAT		PRESEN	-	
2 1281 91 WONTH DAY YEAR	ACTIVE D INACTIVE	·	1975 HNNOWS YE			N
D4 AGENCY PERFORMING INSPECTION	Check of the goods	<u> </u>				
DIA EPA B. EPA CONTRAC	TOR L.C. JOHNSON 4	IVIALHOIKA, I'C.	<sup>•</sup> D С. м	IUNICIPAL 🗆 D. MI	IUNICIPAL CONTRACTOR _	[Name of firm]
LE. STATE D. F. STATE CONTR	LICTOR	Serve of Bray	□ G. O	THER	(Soecity)	Andrew Co. world
OS CHIEF INSPECTOR		OS TITLE			07 ORGANIZATION	08 TELEPHONE NO.
NAHID BROWN		GEO	0606	15T	CCJM	(3/2) 621-3944
09 OTHER INSPECTORS		10 MLE		· · · · · · · · · · · · · · · · · · ·	11 ORGANIZATION	12 TELEPHONE NO.
MATHEW JOSEP	н	CIV	IL EX	NGINEER	CCJM	(312) 621-3944
CLIFF FLORCE	AK	Cr	HEMI	/ S T	E4E	13121663-9415
TANVEER ANJU	'M	Civi	L En	IGINEER	CCTM	(312)621-3944
CHARLES ONYE	ZIA	GI	E010	GIST	CCJM	(312) 621-394
						( )
13 SITE REPRESENTATIVES INTERVIEWE	D	14 TITLE		15ADORÉSS ·		16 TELEPHONE NO
ANNE MOLNAR	ξ	PLANT ENG		650 MILLER Avon Lake	R ROAD OH-44012	(216) 933-1332
RATHY WASKIEL	MICZ .	ENVIRONMEN ENGINEER	NTAL !	15201 CENT DEARBORN,	TURY DRIVE , MI-48120	(3/3) 594-7752
RON STRAUB		PLANT ENG MANAGER	-	650 MILLER AVON LAK	ROAD CE, OH-44012	(216) 933-1347
						( )
						( )
PERMISSION 8:50	OF REPECTION  A.M. TO  1:36 P.M.	19 WEATHER CONDITI		w, 25-	45° F	
IV. INFORMATION AVAILABLE FF		I			J.	
01 CONTACT		02 OF (Agency/Organism			1	03 TELEPHONE NO.
ROD BEAL	HLS	NEDO,	OE	PA	1	12161425-9171
04 PERSON PESPONSIBLE FOR SITE INSP	ECTION FORM		06 ORGA	UNIZATION	~	DO DATE
SANTOSH K. SH	TARMA .	FIT U.S. EPA	· · ·	CJM	(312) 621-3944	7 4 91

# T SEPA

# POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 2 - WASTE INFORMATION

I. IDENTIFICATION

OI STATE OZ STIE NUMBER

OH D 02 06 2 6669

DI PHYSICAL S  DIA SOLID  DIB POWDE  EL C. SLUIDGE  DID, OTHER	. D G.GAS	TONS .	UNKNOWN	B A TOXIC  B B COARO  C RADIOA  D D PERSIS	DE, SOU SIVE DF, INFE CTIVE BG, FLA	UBLE DILHIGH ECTIOUS DIJEXP MMUBLE DIK. REJ TABLE DILINC	
	(Sp+cFy)	NO. OF DRUMS		J			
III. WASTE T			<del></del>	1			
CATEGORY	SUBSTANCE	NAME	01 GROSS AMOUNT	02 UNIT OF MEASURE	03 COMMENTS	<del></del>	
SLU	· SLUDGE			<u> </u>			····
OLW	CALY WASTE	<del></del>	1	{ <del></del>		<del></del>	
SOL	SOLVENTS		UNK NOWN		4.4		
PSO PSO	PESTICIDES		UNKNOWN	ļ	WASTE TY	PES LISTED	ARETAKEN
-000	OTHER ORGANIC C		UNKNOWN		FROM SO	IL SAMPLE F S, TABLE 4	NALYSIS
юс 	INORGANIC CHEMIC	CALS	ļ		KESULT.	S, TABLE 4	<u>-1</u>
ACD	ACIDS					·	
BAS	BASES						
MES	HEAVY METALS		UNKNOWN	[			
V. HAZARDO	لم صدى SUBSTANCES كال	poends for most treatent	ry card CAS Mimorral				
1 CATEGORY	D2 SUBSTANCE N	ME .	DJ CAS NUMBER	O4 STORAGE/DISA	OSAL METHOD -	05 CONCENTRATIO	DO MEASURE OF CONCENTRATIO
	REFER	To TABL	£4-1 OF	THE NARR	ATIVE		
. FEEDSTO	CKS (See Appendix for CAS Mirro	ori)					
CATEGORY	01 FEEDSTOC	X NAME	02 CAS HUMBER	CATEGORY	01 FEEDST	OCK NAME	02 CAS NUMBER
FDS	XYLI	ENE	1330-20-7	FDS	SODIUM E	BISULPHITE	7631-90-
FDS	FERRIC-CH	HLORIDE	7705-08-0	FDS	PROPA		74-98-6
FDS			7664-93-9	FDS		<del></del>	
FD\$	SOPIUM H		1310-73-2	FDS		<i>t</i>	
	1 3000001 7	·- \_ \ / \ / \ / \ / \ / \ / \ / \ / \ /					

PIT SSI, February 28, 1991 DEPA FILE INFORMATION

	<b>POTENTIA</b>	L HAZARDOUS WASTE	SITE		TIFICATION
SEPA SARRA DEGI		INSPECTION REPORT		OHO	02 SITE NUMBER 02062666
PART3-DESC	CRIPTION OF	HAZARDOUS CONDITION	NS AND INCIDENTS	s	
IL HAZARDOUS CONDITIONS AND INCIDI	ENTS		····		
01 M A. GROUNDWATER CONTAMINATION	0	02 OBSERVED (DATE: _		POTENTIAL	D ALLEGED
03 POPULATION POTENTIALLY AFFECTED: .	<del></del>	04 NARRATIVE DESCRIPTI	ON		
REFER TO SECTION	5-2	OF NARRATIVE			
01 B. SURFACE WATER CONTAMINATION 03 POPULATION POTENTIALLY AFFECTED:	93,000	02 D OBSERVED (DATE:	•	POTENTIAL	O ALLEGED
REFER TO SECTION	5-3 (	OF NARRATIVE			
01 D C. CONTAMINATION OF AIR 03 POPULATION POTENTIALLY AFFECTED:	0	02 OBSERVED (DATE: 04 NARRATIVE DESCRIPTION		D POTENTIAL	D ALLEGED
REFER TO SECTION	on 5-4	OF NARRATIVE	E		
01 () (). FIRE/EXPLOSIVE CONDITIONS		02 () OBSERVED (DATE:	)	D POTENTIAL	O ALLEGED
3 POPULATION POTENTIALLY AFFECTED: _		_ 04 NARRATIVE DESCRIPTIO	N .		
REFER TO SECTION	5-5	OF NARRATIVE			
DI BE. DIRECT CONTACT DIS POPULATION POTENTIALLY AFFECTED:	1900	02 D OBSERVED (DATE:		POTENTIAL	□ ALLEGED
REFER TO SECTIO	N 54	OF NARRAT	NE.		
21 B F. CONTAMINATION OF SOIL 4/2		02 OBSERVED (DATE:	2/28/9/_)	O POTENTIAL	O ALLEGED
pen		•			
REFER TO SECTIO	n 4.4	5 OF NARRA	TIUE.		
1 D G. DRINKING WATER CONTAMINATION 3 POPULATION POTENTIALLY AFFECTED:	0	02 D OBSERVED (DATE:		O POTENTIAL	D ALLEGED
REFER SECTION	5-2 an	-d 5-3 OF M	JARRATIUS		
1 1 H. WORKER EXPOSURE/NURY 3 WORKERS POTENTIALLY AFFECTED:	900	02 () OBSERVED (DATE: 04 NARRATIVE DESCRIPTION		POTENTAL	O ALLEGED
REFER SECTION S	-6 OF	NARRATIUE .			
DI. POPULATION EXPOSURE/INJURY  POPULATION POTENTIALLY AFFECTED:	\$3,000	02 OBSERVED (DATE:		POTENTIAL.	C ALLEGED
REFOR SECTION		NARRATIVE.			

- SEPA

# POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT

STIE INSPECTION REPORT

FSCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

L IDENTIFICATION

01 STATE 02 STE NUMBER

0HD 020626669

PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS	
IL HAZAFDOUS CONDITIONS AND INCIDENTS ICONOMIS	
01 D. I. ILLUNGE TO FLORA 02 D. OBSERVED (DATE:) POTENTIAL D. ALLEGE	ΞD
DI NARRATIVE DESCRIPTION THERE IS A POTENTIAL FOR DAMAGE TO FLORA, BECAN	ues
OF SCIL CONTAMINATION ON-SITE.	
01 B K. DAMAGE TO FAUNA 02 D OBSERVED (DATE:) B POTENTIAL D ALLEGE O4 NARRATIVE DESCRIPTION (POLICE ANTHUL OF ADSCRIPT	ED
THERE IS A POTENTIAL FOR DAMAGE TO FAUNA, BECAUSE OF	
SOIL CONTAMINATION ON- SITE.	
01 B L CONTAMINATION OF FOOD CHAIN 02 D OBSERVED (DATE: ) POTENTIAL DIALLEGE 04 NARRATIVE DESCRIPTION	æ
THERE IS A POTENTIAL FOR CONTAMINATION OF FOOL	D
CHAIN BECAUSE OF SOIL CONTAMINATION ON-SITE.	
01 C) M. UNSTABLE CONTAINMENT OF WASTES 02 C) OBSERVED (DATE:) POTENTIAL C) ALLEGE	.D
03 POPULATION POTENTIALLY AFFECTED: 93,000 04 NARRATIVE DESCRIPTION	
PRESENCE OF TCL COMPOUNDS AND TAL ANALYTES IN ON-SITE SO	IL
01 D N. DAMAGE TO OFFSITE PROPERTY 02 D OBSERVED (DATE:) D POTENTIAL D ALLEGE 04 NARRATIVE DESCRIPTION	D O
None, and there is no potential for damage to off-site	
01 8 0. CONTAMNATION OF SEWERS, STORM DRAINS, WWTPS 02 DOBSERVED (DATE:	_
ACCORDING TO FORD, THERE WAS ALLEGED CONTAMINATION	02
OF SEWERS AS A RESULT OF SPILL CASES IN 1979.  OF DE LLEGAL UNAUTHORIZED DUMPING  OF NAME ALLEGED CONTAMINATION OF SEWERS AS A RESULT OF SPILL CASES IN 1979.	02
OF SEWERS AS A RESULT DE SPILL CASES IN 1979.  OF LLEGUL/MAUTHORIZED DUMPING  OF MARGATIVE DESCRIPTION  OF MARGATIVE DESCRIPTION  OF MARGATIVE DESCRIPTION  ACCORDING TO FORD, THERE WAS ALLEGED CONTAMINATION  OF SEWERS AS A RESULT DE SPILL CASES IN 1979.	02
Of SEWERS AS A RESULT OF SPILL CASES IN 1979.  OF LLEGALMAUTHORIZED DUMPING 02 DOBSERVED (DATE:] DOTENTIAL DALLEGED WAS ALLEGED.  None, and no petential.	02
OF SEWERS AS A RESULT DE SPILL CASES IN 1979.  OF LLEGULUNAUTHORIZED DUMPING OF NARFATIVE DESCRIPTION  None, and no petential.  OS DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL OR ALLEGED HAZARDS	02
OF SEWERS AS A RESULT DE SPILL CASES IN 1979.  OI DP ELEGULINAUTHORIZED DUMPING ON NATIONTIVE DESCRIPTION  None, and no petential.  OS DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL OR ALEGED HAZARDS  None.	02
OF SEWERS AS A RESULT OF SPILL CASES IN 1979.  OI OP LLEGALINAUTHORIZED DUMPING ON HARRATIVE DESCRIPTION  None, and no potential of Alleged HAZARDS  None  None  None  None  See Section 2,4 and 5 OF THE NARRATIVE.	02
OF SEWERS AS A RESULT OF SPILL CASES IN 1974.  OF SEWERS AS A RESULT OF SPILL CASES IN 1974.  OI OP ELEGULAMANTHORIZED DUMPING  ON INAPPATIVE DESCRIPTION  None, and no potential.  OF DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL OR ALLEGED HAZARDS  None  IN TOTAL POPULATION POTENTIALLY AFFECTED: 93.000  IN COMMENTS  See Section 2,4 and 5 OF THE NARRATIVE.	02
OF SEWERS AS A RESULT OF SPILL CASES IN 1979.  OI OP LLEGALINAUTHORIZED DUMPING ON HARRATIVE DESCRIPTION  None, and no potential of Alleged HAZARDS  None  None  None  None  See Section 2,4 and 5 OF THE NARRATIVE.	02
OF SEWERS AS A RESULT OF SPILL CASES IN 1974.  OF SEWERS AS A RESULT OF SPILL CASES IN 1974.  OI OP ELEGULAMANTHORIZED DUMPING  ON INAPPATIVE DESCRIPTION  None, and no potential.  OF DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL OR ALLEGED HAZARDS  None  IN TOTAL POPULATION POTENTIALLY AFFECTED: 93.000  IN COMMENTS  See Section 2,4 and 5 OF THE NARRATIVE.	02

SEPA

# POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION

I. IDENTIFICATION

O1 STATE 02 SITE NUMBER

OHD 02 06 2 666

	VEFA -	PART 4 - PERMIT	AND DESCRIP		TION	OHD 026626669
_	II. PERMIT INFORMATION					<del></del>
	OI TYPE OF FERRUT ISSUED	02 PERMIT NUMBER	03 DATE ISSUED	04 EXPIRATION DATE	05 COMMENTS	
	DA NPDES				<u> </u>	
	□ B. UKC		<u> </u>		<u> </u>	
į	□C. AIR		ļ			
_	D. D. RCRA			· · · · · · · · · · · · · · · · · · ·		
-	DE RORA INTERIM STATUS	UNKHOWH	UNKNOWN	UNKNOWN	Since 1	981
	☐ F. SPCC PLAN	UKNOWN	UKNOWN		Since 1	1981
. (	D.G. STATE (Socoty)					
_[	☐ H. LOCAL (Society)	MF - 101	3/1/1989	3/1/1994		discharge City of Lal
	OL OTHER (Specify)	02-4669	10/10/1989		Permit fo	· Pretreatment.
١Į	DJ. NONE	<u> </u>	<u>                                     </u>		<u> </u>	
ſ	IIL SITE DESCRIPTION					
	D. B. PILES  C. DRIUMS, ABOVE GROUND  D. TANK, ABOVE GROUND  E. TANK, BELOW GROUND  D. F. LANDFILL  D. G. LANDFARM  D. H. OPEN DUMP  D. I. OTHER  GOODNERS	(CLDSED) UNKA NKNOWN UNKA 110,500 GALL 14000 GALL	OWN		ECTION L SING RECOVERY TER PRE-	MA BUILDINGS ON SITE 12 00 AREA OF SITE 412 412
		ECTION 2 AN.	D ] OF T	HE NARRA	TIVE.	
┗~	/. CONT.AINMENT			<del></del>	<del></del>	<del></del>
٥	D A. ADEQUATE, SECURE	8. MODERATE	O C. INADEQUA	TE, POOR	D D. INSECURE	L UNSOUND, DANGEROUS
o:	DESCRIPTION OF DRUMS, DIKING, LINERS, BARI THE AREA WHERE		PLACED,	IS DIKE	D AND	Covered

V. ACCESSIBILITY

DI WASTE EASILY ACCESSIBLE: YES ONO DZ COMMENTS

REFER SECTION 5-6 OF THE NARRATIVE

WITH CONCRETE.

VI, SOURCES OF INFORMATION (Con researc references, e.g. sine lifes, surror analysis, resorts)

FORD FILE INFORMATION.

FIT SSI OBSERVATION.

	LIDENTIFICATION					
DI STATE	02 SITE HUMBER					
OHD	020626669					

		POT	ENTIAL HAZAI	RDOUS WAST	TE SI	TE	LID	ENTIFICATION	
	SEPA	1011	SITE INSPECTION REPORT				OI STATE OZ SITE HAMBER		
	VLIA	PART 5 - WATER		-	-	FNTAL DATA	OF	10/020621	6669
			,, 52						
	IL DRINKING WATER SUPPLY	··				·			
-	O1 TYPE OF CHUNNONG SUPPLY (CHICA M REPRESENT)		02 STATUS				٥	3 DISTANCE TO SITE	
	SURFACE	WELL	ENDANGER	ED AFFECTED	)	MONITORED			
_	COMMUNITY . A	₿. 🖸	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	B. 🖸		C. 🖀	A	0.9	x)
	NON-COMMUNITY C. []	Ð. <b>B</b>	D. 🗆	E. D		F. D U NKHOD	) в	. <u>&gt; 3.8</u> (u	ν)
	ML GROUNDWATER								
	01 GROUNDWATER USE IN VICINITY (Ower)		······						· · · · · · · · · · · · · · · · · · ·
	☐ A. ONLY SOURCE FOR DRINKING	B. DRINKING (Other pources predia COMMERCIAL, IN (No other sealer source	DUSTRIAL, IRRIGATIO	(Limited o		INDUSTRIAL, IRRIGAT	NON I	■ D. NOTUSED, UNU	SEARLE
	02 POPULATION SERVED BY GROUND WAT	ER 0	-	03 DISTANCE TO 1	NEARES	T DRINKING WATER V	ÆLL	. > <u>3</u> _(m	a)
_}	04 DEPTH TC: GROUNDWATER	05 DIRECTION OF GRO	N NOW ATER EI OW	DO DEPTH TO AOU	CED.	07 POTENTIAL YIEL		DE SOLE SOURCE	CUNCER
~	_		CADHAIDI FLON	OF COHCERN	u- E.A	OF AQUIFER			
1	(n)	<u> </u>	<del></del>	20	(h)	2×10-3	(ppd).	C YES	NO NO
.t	DO DESCRIPTION OF Y/ELLS (mounting unexpe.	death, and location relicion to	Donations and buildings	!		<del></del>		<del></del>	
	REFER SECT			RRATIVE					
}	TES COMMENTS LOW P	ECHARGING 1 ERMEABILITY LAYER AND	OF TOY SOL	<b>■</b> NO	EA IMENT	s No str	rean Tu	ns or any ground	other wate:
L	IV. SURFACE WATER								
1	01 SURFACE WATER USE (Check one)  8 A. RESERVOR, RECREATION)	☐ B. IRRIGATION	1, ECONOMICALLY	🗆 С. СОММ	ERCIA	L, INDUSTRIAL	0.0	D. NOT CURRENTLY	Y USED
	(DANKING WATER SOURCE)	IMPORTAN'	TRESOURCES	<del></del>		· · · · · · · · · · · · · · · · · · ·			
}	02 AFFECTED/POTENTIALLY AFFECTED BOX	DIES OF WATER			•				
I	NAME:					AFFECTED		DISTANCE TO SIT	Ε
	LAKE ERIE	•				_		0.9	
7	BLACK RIVER					<u>D</u>	_	2.7	(ml)
ł	DEACK KINGS	<del></del>		<del></del>					— (mj)
L									(ml)
1	V. DEMOGRAPHIC AND PROPERTY	INFORMATION				_			
Г	PHITIW HISTAULICE LODE 10				02 [	NSTANCE TO NEARES	T POPU	LATION	
	ONE (1) MILE OF SITE TWO  A 2470 B.	(2) MILES OF SITE 50 2 5 HO, OF PERSONS		MILES OF SITE 8435 D. OF PERSONS			6 · /	(mi)	
1	03 NUMBER OF BUILDINGS WITHIN TWO (2) I	OLES OF SITE		04 DISTANCE TO NE	AREST	OFF-SITE BUILDING			<del></del>
	1769					0.1			
L							(m	vi)	
1	THIS FACILITY				•				/

INDUSTRIAL/COMMERCIAL AREA.

	<b>-</b> r	ΛC
~	<b>├</b> ~}·	$\Delta \Delta$
	<b>—</b> I	1 1

# POTENTIAL HAZARDOUS WASTE SITE

I. IDENTIFICATION

	SEPA .	SITE INSPE PART 5 - WATER, DEMOGRAP	CTION REPORT PHIC, AND ENVIRONM	IENTAL DATA	01 STATE 02 SITE MUMBER OHD 0206 26669
_	VI. ENVIRONMENTAL INFORMATION				
	01 PERMEABILITY OF UNSATURATED ZONE ICA	ec <b>8</b> 8. 10 <sup>-4</sup> – 10 <sup>-6</sup> cm/sec	□ C. 10 <sup>-4</sup> ~ 10 <sup>-3</sup> cm/sec	D D. GREATER T	THAN 10 <sup>-3</sup> cm/sec
	02 PERSEABILITY OF BEDROCK (Chack and)				
	A IMPERMEABLE	/sec) /10 <sup>-4</sup> - 10 <sup>-6</sup> physec)	110-2-10-4		VERY PERMEABLE Greater man 10 <sup>-2</sup> convises)
	04 DEF 15-50 (th)	PTH OF CONTAMINATED SOIL ZONE  UNKNOWN IN	UNK N	1000	
	06 NET PRECIPITATION 07 ONE	E YEAR 24 HOUR RAINFALL	08 SLOPE DIF	RECTION OF SITE SLO	OPE TERRAIN AVERAGE SLOP
	4·5 (in)	2 · 15 (in)	<u>8.02</u> %	N	0.04
	STE IS INYEAR FLOODPLA	IN D STE IS ON BARF	RIER ISLAND, COASTAL HK	3H HAZARD AREA, R	EVERINE FLOODWAY N/A
ı	11 DISTANCE TO WETLANDS (3 200 manuary		12 DISTANCE TO CRITICAL	•	•
	ESTUARINE	OTHER			(mi)
L	A	B. > / (ml)	ENDANGERED SP	PECIES: UNICA	10 W M
1	13 LAND USE IN VICINITY				
	DISTANCE TO:	RESIDENTIAL AREAS; NATION FORESTS, OR WILDLIS		AGRICU PRIME AG LAND	ILTURAL LANOS AG LANO
	/- (mi)	B. 0·1	(ml) C	UNKHOWA	mi) D. 1-5 (mi)
ľ	14 DESCRIPTION OF SITE IN RELATION TO SURRO	XUNDING TOPOGRAPHY			
		•			
l	Re	FER TO APPEN	DIX: A		
	, <del>-</del>				
		•			•
1					
		•			
VI	L SOURCES OF INFORMATION	de relevençõe, e.S., liste Mos, semple eneryes, re	own)		
	U·s·EP,	A FILE INFOR	MATION		
	FIT S	ς Γ			
		EPT. OF COMMER	CE CLIMAT	IC MAPS	•
	U 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		/		

)	9	<b>FPA</b>

# POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT

		TEICATION
i	OI STATE	02 SITE NUMBER
١	OHD	020626669

	P/	ART 6 - SAMPLE AND FIELD INFORMATION	
IL SAMPLES TAKEN		•	
SAMPLE TYPE	01 NUMBER OF SAMPLES TAKEN	02 SUMPLES SENT TO	OJ ESTIMATED DATE RESULTS AVALABL
GROUNDWATER			
SURFACE WATER		·	
WASTE			
AIR			
RUNOFF			
SPILL			
SOIL	9	TCL - NET, BARTLETT, IL. TAL - DATACHEM, SALT LAKE CITY OTAH.	NOW AVAILABLE
VEGETATION			
OTHER			
IIL FIELD MEASUREMENTS TA	IKEN		<del>-</del>
OI TYPE	02 COMMENTS		
OVA	No RE	FADINGS DEVIATING FROM BACKGROUND	LEVELS
Oxygen METER	No R	EADINGS DEVIATING FROM BACKGROUND	LEVELS
RADIATION MONITOR		FADINGS DEVIATING FROM BACKGROUNDL	
HYDROGEN CYANIDE MONITOR	1	ADINGS DEVIATING FROM BACKGROUND	
EXPLOSIMETER	1	FAUING DEVIATING FROM BACKGROUNS	
IV. PHOTOGRAPHS AND MAPS			
DI TYPE (3) GROUND () AERIAL		02 H CUSTOOY OF Ecology & Environment, Inc., Chi	cayo. IL.
03 MAPS 04 LOCATION  12 YES  12 NO		= Inc. Chicago, Illinois.	
V. OTHER FIELD DATA COLLEC	CTED (Provide mersons asso	Tiplical/	

None

VI. SOURCES OF INFORMATION (Can apocific references, e.g., state fine, among analysis, records)

FIT SITE INSPECTION, 2/28/91

		POT	TENTIAL HAZ	ARDOUS WASTE SITE			ICATION
SEPA				CTION REPORT	01:		Z SITE NUMBER
VLIA			PART 7 - OWN	IER INFORMATION	٥	HD	02062666
IL CURRENT OWNER(S)				PARENT COMPANY	D0452041		<del></del>
OI NUME		02 0	+B MUMBER	OB NUME	<del></del>		09 C+8 NUMBER
FORD MOTOR CO	•		UNKNOWN	FORD MO	TOR Co.		
03 STREET ACORESS (P O. Bal NO P. MC.)			04 SIC COO€	10 STREET ADDRESS (P.O. and	, AFD 4, arc.)		11 SIC COD€
650 MILLER ROAL			3713	15201 (enti	1		
os cary	OG STAT	-1		12 CTY		1	48120
AVON LAKE	ОН		4012	DEARBORN		MI	
N/A		020	+8 NUMBER	OB NAME .			09 C+B NUMBER
<u></u>		٫ـــــــــــــــــــــــــــــــــــــ		N/A	<del></del>		
03 STREET ACKORESS (P.O. BOL MO P. MC)		- 1	04 SIC COOE	10 STREET ADDRESS IP.O. Box.	NFD F. HC.)		115C COOE
os arr	OG STAT	=1022	0.000	12 017	10.	OT ITE	14 ZP CODE
05 (4) 1	امادها	10,2	ir cook	12017	\\ \ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \	اعتماده	1422-000
		107.0	+B NUMBER	08 NAME		<del> </del> ,	REBMUMBER
OI NULE		1023	TB NOMBEN	US NO.		]`	D D T B NOM GER
OJ STREET ALXORESS (F.O. BOL. MO F. orc.)		-1	04 SIC COOE	10 STREET ADORESS (P.O. BOL	NO1, HE		115C COOE
		- 1					1
os atr	00 STATE	07 ZF	° COO€	12 011	13	STATE	4 ZP 000€
	}						
01 NAME	<del> </del>	02 D+	BNUMBER	D8 NAME	·····	0	90+8 NUMBER
		ł					
03 STREET ADORESS (P.O. BOL AFD P. HE)		I	4 SIC CODE	10 STREET ADDRESS (F.O. BOL.	V-D /, e/C.)		11 SIC COD€
		- 1					l
0s CTY	06 STATE	07 Z)F	° COO€	12 CITY	13:	STATE 1	4 ZP COO€
	1	•		•			
IL PREVIOUS OWNER(S) (Un room room in	ø.			IV. REALTY OWNER(S)	policable; But most record first	<del></del>	
FRUEHAUF CORI		02 D+	B NUMBER	OI NAME .		0:	2 D+8 NUMBER
FRUEHAUF CORP	•			UNKNOL	77		
03 STREET ADDRESS (F.O. Box, AFD F. sec.)		To	4 SIC CODE	03 STREET ADDRESS (F.O. Mac.	FOI. HEJ		04 SIC CODE
650 MILLER ROA					~		
AVON LAKE	06 STATE			os arr	06 S	TATE 0	7 20P CODE
DI NUE	104		O/L	01 NAVE			7 0 + 8 W 14 0 F B
· · · · · · · · · · · · · · · · · · ·	ď	UZ UTE	, imoch			"	O+B NUMBER
DI STREET ADORESS (P.O. DAL 16FO P. DEL)		Ta	I SIC CODE	03 STREET ADDRESS (P.O. Aug. N	De me i		04 SIC COD€
The second second second St. 100 miles and the second			1				
\$ any	OS STATE	07 20P C	∞0€	os CTY	00 S	TATE 07	ZIP CODE
	1 1		l		ļ	- }	
1 NUE	<del></del>	02 D+E	NUMBER	OI NAME	<del></del>	02	D+B NUMBER
	1						
2		100	sir cone	22 CTREET ADDRESS (# 0 8- #0	14 1		104 00 0005

05 CTY

DO STATE OF ZIP CODE

*!*• ·

FIT SSI INTERVIEW, 2/28/9)

DESTATE OF ZIP CODE

V. SOURCES OF INFORMATION (CAN ADDITION OF A DESCRIPTION OF A DESCRIPTION

ಜರ್ಞ

	•
9	<b>EPA</b>

# POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 8-OPERATOR INFORMATION

LIDENTIFICATION				
OI STATE	02 SITE MUMBER			
OHD	020626669			

	\/ LI / \			PART 8 - OPERAT	UND	020626607		
ļ	II. CURRENT OPERATOR	Provide & different from	• • • • • • •		OPERATOR'S PARENT COMPANY			
	OI NAME			02 D+B NUMBER	FORD MOTOR CO.	<del></del>	11 D+B NUMBER	
7	OS CITY OG STREET ADDRESS (P.O. BOL. RED P. MC.)			04 SIC CODE	12 STREET ADDRESS IP.O. BOX, AFDI. OCI 15201 (entury Drive			
_	os any		OS STATE	07 ZIP COOE	DEARBORN		16 ZP CODE 4-8/20	
7	OB YEARS OF (SPERATION O	9 NAME OF OWNER	·					
-	IIL PREVIOUS OPERATO	R(S) (List most record for	C pro-ess evry	8 (Milward from sweet)	PREVIOUS OPERATORS' PARENT COM	PANIES .	V applicable)	
Ì	OI NAME	UF COR		DZ D+B NUMBER	10 NME UN KNOW N		11 D+B NUMBER	
7	650 MILLE	ROAD	,	04 SIC COOE	12 STREET ADDRESS (P.O. Box, AFD F. oc.)		13 SIC CODE	
44	AVON LAKI		OB STATE	94401Z	14 CITY	15 STATE	16 ZIP CODE	
	08 YEARS OF OPERATION OF	HAME OF OWNER D		PERIOD		·	<del></del>	
	UNKNO	WN	O	2 D+8 NUMBER	10 NAME		110+B NUMBER	
•	DJ STREET ALIONESS (F.D. BOL A	VD1. MCJ		04 SIC COOE .	12 STREET ADDRESS (P.O. BOX, RFD P, MC.)	المحدد المحدد	13 SIC COO€	
	05 CTY		06 STATE C	77 ZIP CODE	14 CITY	15 STATE	16 ZIP CODE	
-   	DE YEARS OF OPERATION OF	9 NAME OF OWNER D	URING THIS	PERIO0	· ·	البسسميدك.	· · · · · · · · · · · · · · · · · · ·	
•	) I NALÆ	<del></del>	0	2 D+B NUMBER	10 NAME		11 D+B NUMBER	
	DI STREET ANORESS (P.O. BOX. A	FD 4. esc.)	<del></del>	04 SIC COOE	12 STREET ADDRESS (P.O. BOX, NFD P, oc.)		13 SIC CODE	
ľ	os atr		OG STATE O	7 23P COOE	14 CTY	15 STATE	16 ZIP CODE	
<u>'</u>  [	08 YEARS OF OPERATION OF	NAME OF OWNER D	URING THIS	PERICO		1	·	
	IV. SOURCES OF INFORM	IATION (Cre specific )	works, s.g	, ataro Bos, Sample analysis, n	aporta)			
					•			
		FIT S	ITE	INTERVIE	W, 2/28/9)			
Ì								
					ţ.			
					•			
1								

1	_			
		<b>,</b>	DV	
		-		

# POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT ART 9 - GENERATOR/TRANSPORTER INFORMATION

L. IDENTIFICATION
O1 STATE 02 SITE NUMBER
OHD 0206 2666 9

				CANSPORTER INFOR			
IL ON-SITE GENERATOR							·
OI MANGE		020	BNUMBER	T			<del></del> -
FORD MOTOR CO.		U,	NKNOW N				
STREET ADORESS (P.O. BOA, AFD F, orc.)			04 SIC CODE				
650 MILLER ROAD		]	3713		•		
sary ,	06 STAT	E 07 ZV	CODE				
AUON LAKE	OH	14	4012				
L OFF-SITE GENERATOR(S)							
None		02 D+	BNUMBER	OI NAME		0	20+8 NUMBER
STREET ADDRESS (P.O. BOX, RFD F, erc.)		10	4 SIC COOE	03 STREET ADDRESS IP.O	Bos, AFD F, etc.)		04 SXC 00000
		- 1		1			
an	06 STATE	07 ZP	CODE	05 CTY	oc	STATE	7 ZIP COOE
NAME	l	02 0+	B NUMBER	01 NAME		0	2 D+8 NUMBER
STREET ADDRESS (P. J. BOX, AFD P. HC.)		1	4 SIC COD€	03 STREET ADDRESS (P.O.	BOL PFD F, erc.)		04 SIC COO€
arr	OG STATE	07 ZIP	CO0€	05 CITY	00	STATE	ZP COO€
. TRANSPORTEFYS)	<u></u>	<u></u>					<del> </del>
None	<del></del>	02 D+E	NUMBER	01 NAME		02	D+B NUMBER
STREET ACORESS (P.O. BOX, AFD #, MC.)		04	SIC CODE	03 STREET ADORESS (P.O.	305. NFD 1, MCJ		04 SC COOE
मा <b>र</b>	OS STATE	07 ZDP (	×××××××××××××××××××××××××××××××××××××	os aty	06	STATE OF	200€
w€		02 D+8	NUMBER	O1 NAME		02	D+B NUMBER
TPEET ADDRESS (P.O. BOL, APD P. MC.)		04	SIC CODE	03 STREET ADDRESS (P.O. I	ins. NFD #, orc.)		04 SC COO€
TY	06 STATE	07 DP C	××××××××××××××××××××××××××××××××××××	os atr	06.5	TATE 07	ZP COD€
OURCES OF INFORMATION (CAN ADMINISTRATION)		G., Mario M	les, kample anayals, rep	<b>~~~</b>		! 	

FORD FILE INFORMATION .

		POTENTIAL HAZARDOUS WASTE SITE		L IDENTIFICATION
	<b>\$EPA</b>	SITE INSPECTION REPORT PART 10 - PAST RESPONSE ACTIVITIES		01 STATE 02 SITE NUMBER OHD 020626669
	IL PAST RESPONSE ACTIVITIES			
	01 D.A. WATER SUPPLY CLOSED	O2 DATE	03 AGENCY	
	04 DESCRIPTION N/A			
	01 D B. TEMPORARY WATER SUPPLY PROVI	VIDED 02 DATE	03 AGENCY	
	04 DESCRIPTION N/A			
1	01 D.C. PERMANENT WATER SUPPLY PROVI	70ED 02 DATE	03 AGENCY	
	M/A			
۱-	01 C. D. SPILLED MATERIAL REMOVED 04 DESCRIPTION	02 DATE	03 AGENCY	
	. N/A	· · · · · · · · · · · · · · · · · · ·		
-	01 D.E. CONTAMINATED SOIL REMOVED 04 DESCRIPTION	02 DATE	03 AGENCY	
	04 DESCRIPTION N/A			
•	01 D F. WASTE REPACKAGED 04 DESCRIPTION	02 DATE	03 AGENCY	
	N/A			
	01 D. G. WASTE DISPOSED ELSEWHERE 04 DESCRIPTION /	02 DATE	03 AGENCY	
	N/A			
• [	01 C) H. ON SITE BURIAL 04 DESCRIPTION ,	02 DATE	03 AGENCY.	
	. P/A			
1	01 D.L. IN SITU CHEMICAL TREATMENT 04 DESCRIPTION	02 DATE	03 AGENCY.	
	r/A	. O2 DATE	<del></del>	· · · · · · · · · · · · · · · · · · ·
	01 C.I.J. IN STU BIOLOGICAL TREATMENT 04 DESCRIPTION	O2 DATE	03 AGENCY	
_	~/A			
	01 C) K. IN SITU PHYSICAL TREATMENT 04 DESCRIPTION N/	02 DATE	03 AGENCY _	
	N/A			<del></del>
	01 () L. ENCAPSULATION 04 DESCRIPTION /	D2 DATE	03 AGENCY	
	of description N/A			
1	01 [] M. EMERGENCY WASTE TREATMENT	02 DATE	03 AGENCY _	
	04 DESCRIPTION N/A	•		
	01 [] N. CUTOFF WALLS 04 (XESCRIPTION /	02 DATE	03 AGENCY	
	A/A			
	01 () O. EMERGENCY DIKING/SURFACE WATER 04 ()ESCRIPTION /	ER DIVERSION 02 DATE	03 AGENCY _	
	r/A			
I	01 D.P. CUTOFF TRENCHES/SUMP 04 DESCRIPTION	02 DATE	D3 AGENCY.	
	N/A			
	01 D.Q. SUBSURFACE CUTOFF WALL 04 DESCRIPTION	02 DATE	03 AGENCY _	
1	N A	- -		•

EPA FORM (070-13(7-81)

Ω	<b>r</b> ~	$\Box \Lambda$
~	-	$P\Delta$

# POTENTIAL HAZARDOUS WASTE SITE

	I. IDENTIFICATION					
1	OI STATE	02 SITE NUMBER				
		02062666				

	SEPA	SITE INSPECTION REPORT PART 10 - PAST RESPONSE ACTIVITIES	OHD 020626669
-	# PAST RESPONSE ACTIVITIES	<del></del>	
	01 D R. BARFIER WALLS CONSTRUCTED 04 DESCRIPTION N/A		03 AGENCY
	01 D S. CAPPING/COVERING 04 DESCRIPTION N/A		03 AGENCY
	01 D.T. BULK TANKAGE REPAIRED 04 DESCRIPTION N/A		03 AGENCY
	01 D U, GROUT CURTAIN CONSTRUCTED 04 DESCRIPTION N/A		03 AGENCY
	01 CI V. BOTTOM SEALED 04 DESCRIPTION N/A	. •	03 AGENCY
	01 D. W. GAS CONTROL 04 DESCRIPTION N/H		03 AGENCY
	01 D X FIRE CONTROL 04 DESCRIPTION N/A-		03 AGENCY
	O1 DY, LEACHATE TREATMENT O4 DESCRIPTION N/A		03 AGENCY
	01 CI Z AREA EVACUATED 04 DESCRIPTION N/A		03 AGENCY
	01 (1. ACCESS TO SITE RESTRICTED 04 DESCRIPTION N/A	:	03 AGENCY
	01 D 2 POPULATION RELOCATED 04 DESCRIPTION N/A	02 DATE	03 AGENCY
	01 () 3. OTHER REMEDIAL ACTIVITIES 04 DESCRIPTION  NON E	O2 DATE	03 AGENCY
		•	
		•	

ML SOURCES OF INFORMATION (Cre-mooth) price mooth price

FIT SITE INFORMATION, 2/28/91 SITE OWNER INFORMATION

SEPA

#### POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 11 - ENFORCEMENT INFORMATION

L IDENTIFICATION

DI STATE OF SITE NUMBER
OHD 020626669

II. ENFORCEMENT INFORMATION

DI PAST REGULATORY/ENFORCEMENT ACTION YES INO

02 DESCRIPTION OF FEDERAL STATE, LOCAL REGULATORY/ENFORCEMENT ACTION

SEE SECTION 2 OF NARRATIVE .

IIL SOURCES OF INFORMATION ICLO ADOCCE PRIPADED & 9 . SIGIO HOS, ADDROSS, PROPADED

FIT SITE INSPECTION, 2/28/91

C

APPENDIX D

FIT SITE PHOTOGRAPHS

SITE NAME: FORD MOTOR COMPANY - OHIOTRUCK PLT. PAGE 1 OF 9

U.S. EPA ID: OHDO20626669 TDD: F05-9007-012 PAN: FOHO646 SA

יביים וביים ו

DATE: 2/28/91

TIHE: 1210

DIRECTION OF PHOTOGRAPH:

SW

WEATHER CONDITIONS: .


SNOW

25 -45°F

PHOTOGRAPHED BY: NAHLD BROWN

SAMPLE ID (if applicable):





DATE: 2 28/91

OLD POND.

TIHE: 1210

DIRECTION OF PHOTOGRAPH:

SW

WEATHER CONDITIONS: SNOW.

25-45°F

PHOTOGRAPHED BY: NAHID BROWN

SAMPLE ID (if applicable): 51

DESCRIPTION:





SITE NAHE: FORD MOTOR COMPANY - OHIOTRUCK PLT. PAGE 2 OF 9

U.S. EPA ID: OHDO20626669 TDD: F05-9007-012 PAN: FOHO646 SA

DATE: 2/28/91

TIME: 123c

DIRECTION OF PHOTOGRAPH:

E

WEATHER CONDITIONS: ,

SNOW

25 -45°F

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):

52



DESCRIPTION:

CLOSE-UP VIEW OF SAMPLE LOCATION SZ. NEAR PAINT.

DATE: 2 28/91

TIHE: 1230

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:

25-45°F

PHOTOGRAPHED BY:
NAHID BROWN

SAMPLE ID (if applicable):

S2



DESCRIPTION:

PERSPECTIVE VIEW OF SAMPLE LOCATION SZ.

FIELD PHOTOGRAPH: LOG SHEE.

SITE NAME: FORD MOTOR COMPANY OHIO TRUCK PLT PAGE 3 OF 9

U.S. EPA ID: 0HD020626669 TDD: F05-9007-012 PAN: F0H0646SA

Maria Comment of the Maria of the Comment of the Co

DATE: 2/28/91

TIME: 1230

DIRECTION OF PHOTOGRAPH:

NE

WEATHER CONDITIONS: ,

SNOW


25-45°F

PHOTOGRAPHED BY: NAHID BROWN

SAMPLE ID (if applicable):

DESCRIPTION: CLOSE-UP VIEW OF SAMPLE LOCATION S3, WEAR

LOADING DOCK AREA SOUTH OF PAINT SHOP.



TIME: /230

DIRECTION OF

PHOTOGRAPH: NE

WEATHER

CONDITIONS: SNOW, 25-45°F

PHOTOGRAPHED BY: NAHID BROWN

SAMPLE ID

(if applicable): 53

DESCRIPTION: PERSPECTIVE

VIEW OF SAMPLE

LOCATION 53.



FIELD PHOTOGRAPHI LOG SHEET

SITE NAHE: FORD MOTOR COMPANY - OHIOTRUCK PLT. PAGE 4 OF 9

U.S. EPA ID: OHDO20626669 TDD: F05-9007-012 PAN: FOHO646 SA

DATE: 2/28/91

TIME: 1310

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS: ,


SNOW

25 -45°F

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): \$4

DESCRIPTION:



CLOSE-UP VIEW OF SAMPLE LOCATION S4.

DATE: 2 28/91

TIHE: 1310

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:

25-45°F

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): \$4



DESCRIPTION:

PERSPECTIVE VIEW OF SAMPLE LOCATION S4.

#### FIELD PHOTOGRAPHY LOG SHEET

SITE NAHE: FORD MOTOR COMPANY - OHIOTRUCK PLT. PAGE 5 OF 9

U.S. EPA ID: OHD020626669 TDD: F05-9007-012 PAN: F0H0646 SA

DATE: 2/28/91

TIHE: 1415

DIRECTION OF PHOTOGRAPH:

NE

WEATHER CONDITIONS: ,

SNOW

25 -45°F

PHOTOGRAPHED BY:

NAHIO BROWN.

SAMPLE ID (if applicable): \$5

> 5



DESCRIPTION:

CLOSE- UP VIEW OF SAMPLE LOCATION S5, FORMER LAGOON

DATE: 2 28/91

TIHE: 1415

DIRECTION OF PHOTOGRAPH:

SW

VEATHER
CONDITIONS:
SNOW

25-45°F

PHOTOGRAPHED BY:

SAHPLE ID (if applicable):

S 5

DESCRIPTION:



PERSPECTIVE VIEW OF SAMPLE LOCATION S5.

FIELD PHOTOGRAPHY LOG SHEET

SITE NAME: FORD MOTOR COMPANY - OHIOTRUCK PLT. PAGE 6 OF 9

U.S. EPA ID: OHDO20626669 TDD: F05-9007-012 PAN: FOHO646 SA

DATE: 2/28/91

TIME: 1445

DIRECTION OF PHOTOGRAPH:

N

WEATHER CONDITIONS: ,

SNOW

25 -45°F

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): \$ 6



DESCRIPTION:

CLOSE-UP VIEW OF SOIL SAMPLE LUCATION S6, NEAR

DATE: 2 28/91

TIHE: 1445

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SNOW

25-45°F

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):



DESCRIPTION:

BERSPECTIVE VIEW OF SOIL SAMPLE LOCATIONS S6.

SITE NAHE: FORD MOTOR COMPANY - OHIOTRUCK PLT. PAGE 7 OF 9

U.S. EPA ID: OHDO20626669 TDD: F05-9007-012 PAN: FOHO6465A

DATE: 2/28/91

TIME: 1450

DIRECTION OF PHOTOGRAPH:

N

WEATHER CONDITIONS: ,

SNOW

25 -45°F

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):
S: 7



DESCRIPTION:

CLOSE-UP VIEW OF SOIL SAMPLE LOCATION ST, SOUTH

DATE: 2/28/91

TIHE: 1450

DIRECTION OF PHOTOGRAPH:

N.W

WEATHER
CONDITIONS:
SNOW

25-45°F

PHOTOGRAPHED BY:
NAHID BROWN

SAMPLE ID (if applicable):

S 7



DESCRIPTION:

PERSPECTIVE VIEW OF SOIL SAMPLE LOCATION ST.

FIELD PHOTOGRAPHY LOG SHEET

SITE NAME: FORD MOTOR COMPANY OHIO TRUCK PLT PAGE 8 OF 9

U.S. EPA ID: OH DO20626669 TDD: F05-9007-012

PAN: FOHO6465A

DATE: 2/28/91

TIME: 1505

DIRECTION OF PHOTOGRAPH: SE

WEATHER CONDITIONS: ; SNOW

25-45°F

PHOTOGRAPHED BY: NAHID BROWN

SAMPLE ID (if applicable): 58



DESCRIPTION: CLOSE-UP VIEW OF SOIL SAMPLE LOCATION

S8, BACKGROUND FACING PAINT SHOP.

DATE: 2/28/91

TIME: 1505

DIRECTION OF PHOTOGRAPH: NW

CONDITIONS: SNOW, 25-45°F

PHOTOGRAPHED BY: NAMID BROWN


SAMPLE ID

(if applicable): 58

DESCRIPTION: PERSPECTIVE

VIEW OF SOIL SAMPLE

LOCATION S8.



01101	MOTOR COMPANY OHIO TRUCK PLT PAGE 9 OF 9
	020626669 TDD: F05-9007-012 PAN: F0H06+65
DATE:	
TIHE:	
DIRECTION OF PHOTOGRAPH:	
VEATHER CONDITIONS: ,	
PHOTOGRAPHED BY:	
SAMPLE ID (if applicable):	
DESCRIPTION:	Photograph did not develop.
DATE:	
DATE:	
TIME: DIRECTION OF .	
TIHE: DIRECTION OF . PHOTOGRAPH: WEATHER	
DIRECTION OF PHOTOGRAPH:  WEATHER CONDITIONS:	

## APPENDIX E

U.S. EPA TARGET COMPOUND LIST AND TARGET ANALYTE LIST QUANTITATION/DETECTION LIMITS

## ADDENDUM A

ROUTINE ANALYTICAL SERVICES
CONTRACT REQUIRED DETECTION AND QUANTITATION LIMITS

# Contract Laboratory Program Target Compound List Quantitation Limits

· ·	- · - •		SOIL SEDIHENT
СОНРОИНО	CAS #	VATER	SLUDGE
Chloromethane	74-87-3	10 ug/L	10/1/
Bromomethane	74-83-9	10	10 ug/Kg 10
Vinyl chloride	75-01-4	10	10
Chloroethane	75-00-3	. 10	10
Hethylene chloride	75-09-2	5	5
Acetone	67-64-1	10	5
Carbon disulfide	75-15-0		5
1,1-dichloroethene	75-35-4	5 5	5
1,1-dichloroethane	75-34-3		5 5
1,2-dichloroethene (total)	540-59-0	5 5 5	
Chloroform	67-66-3	5	5 5
1,2-dichloroethane	107-06-2	5	5
2-butanone (HEK)	78-93-3	10	10
1,1,1-trichloroethane	71-55-6	5	5
Carbon tetrachloride	56-23-5	5 5	5 .
Vinyl acetate	108-05-4	10	10
Bromodichloromethane	75-27-4	5	5
1,2-dichloropropane	78-87-5	5	5
cis-1,3-dichloropropene	10061-01-5	5	5
Trichloroethene	79-01-6	5	5
Dibromochloromethane	124-48-1	5	5
1,1,2-trichloroethane	79-00-5	5	5
Benzene	71-43-2	. 5 . 5	5
Trans-1,3-dichloropropene	10061-02-6	. 5	. 5
Bromoform	75-25-2	5	. J 5
4-Hethyl-2-pentanone	108-10-1	10 -	10
2-Hexanone	591-78-6	10	10
Tetrachloroethene	127-18-4	5	5 .
Tolene ·	108-88-3	5	5
1,1,2,2-tetrachloroethane	79-34-5	5	· 5
Chlorobenzene	108-90-7	5	5
Ethyl benzene	100-41-4	5 5	5
Styrene	100-42-5		5
Xylenes (total)	1330-20-7	· 5	5 5
	•		<i>.</i>

# Table A Contract Laboratory Program Target Compound List Semivolatiles Quantitation Limits

СОНРОИНО	CAS #	WATER	SOIL SEDIHENT SLUDGE
Phenol	108-95-2	10 ug/L	220
bis(2-Chloroethyl) ether	111-44-4	10 dg/L	330 ug/Kg
2-Chlorophenol	95-57-8	10	330
1,3-Dichlorobenzene	541-73-1	10	330
1,4-Dichlorobenzene	106-46-7	10	330 ,
Benzyl Alcohol	100-51-6	10	330
1,2-Dichlorobenzene	95-50-1	10	330
2-Hethylphenol	95-48-7		330
bis(2-Chloroisopropyl) ether	108-60-1	10	330
4-Hethylphenol	106-44-5	10	330
N-Nitroso-di-n-dipropylamine	621-64-7	10	. 330
Hexachloroethane	67-72-1	10	330
Nitrobenzene .	98-95-3	10	330
Isophorone	78-59-1	10	330
2-Nitrophenol	88-75-5	10	330
2,4-Dimethylphenol		10	330
•	105-67-9	10	330
Benzoic Acid	65-85-0	50	1600 ·
bis(2-Chloroethoxy) methane	111-91-1	10	330
2,4-Dichlorophenol	120-83-2	10	330
1,2,4-Trichlorobenzene	120-82-1	10	330
Naphthalene	91-20-3	10	330
4-Chloroaniline	106-47-8	10	330
Hexachlorobutadiene	87-68-3	10	300
4-Chloro-3-methylphenol	59-50-7	10	
2-Hethylnaphthalene	91-57-6	10	330
Hexachlorocyclopentadiene	77-47-4	10	330
2,4,6-Trichlorophenol	88-06-2	10	330
2,4,5-Trichlorophenol	95-95-4	50	330
2-Chloronaphthalene	91-58-7	10	1600
2-Nitroaniline	88-74-4	50	330
Dimethylphthalate	131-11-3	10	1600
Acenaphthylene	208-96-8		330
2,6-Dinitrotoluene	606-20-2	10	330
3-Nitroaniline	99-09-2	10	330
Acenaphthene	83-32-9	50	1600
•		10	330 .
2,4-Dinitrophenol 4-Nitrophenol	51-28-5	50	1600
Dibenzofuran	100-02-7	50 ·	1600
	132-64-9	10	330
2,4-Dinitrotoluene	. 121-14-2 84-66-2	10	330 ·
Diethylphthalate		10	330
4-Chlorophenyl-phenyl ether	7005-72-3	10	330

Table A
Contract Laboratory Program
Target Compound List
Semivolatiles Quantitation Limits

			SOIL SLUDGE
COHPOUND	CAS #	VATER	SEDIHENT
Fluorene	86-73-7	10 ug/L	220
4-Nitroaniline	100-01-6	50	330 ug/Kg
4,6-Dinitro-2-methylphenol	534-52-1	50	1600
N-nitrosodiphenylamine	86-30-6	10	1600
4-Bromophenyl-phenylether	101-55-3	10	330 .
Hexachlorobenzene	118-74-1	10	330
Pentachlorophenol	87-86-5	50	330 1600
Phenanthren <b>e</b>	85-01-8	10	330
Anthracene	120-12-7	10	330
Di-n-butylphthalate	84-74-2	10	330
Fluoranthene	206-44-0	10 .	330
Pyrene ·	129-00-0	10	330
Butylbenzylphthalate	85-68-7	10	. 330
3,3'-Dichlorobenzidine	91-94-1	20	
Benzo(a)anthracene	56-55-3	10	660
Chrysene	218-01-9	10	330
bis(2-Ethylhexyl)phthalate	117-81-7	10	330
Di-n-octylphthalate	117-84-0	10	330
Benzo(b)fluoranthene	205-99-2	10	330
Benzo(k)fluoranthene	207-08-9	10	330
Benzo(a)pyrene	50-32-8	10	330
Indeno(1,2,3-cd)pyrene	193-39-5	10	330
Dibenz(a,h)anthracene	53-70-3	10	330
Benzo(g,h,i)perylene	191-24-2	10	330 330

# Table A Contract Laboratory Program Target Compound List Pesticide and PCB Quantitation Limits

·			SOIL SEDIHENT
COHPOUND	CAS #	VATER ·	SLUDGE
alpha-BHC	319-84-6	0.05 ug/L	8 ug/Kg
beta-BHC	319-85-7	0.05	8
delta-BHC	319-86-8	0.05	8
gamma-BHC (Lindane)	58-89-9	0.05	8
Heptachlor	76-44-8	0.05	8
Aldrin	309-00-2	0.05	8
Heptachlor epoxide	1024-57-3	0.05	8 .
Endosulfan I	959-98-8	0.05	8
Dieldrin	60-57-1	0.10	16
4,4'-DDE	72-55-9	0.10	16
Endrin	72-20-8	0.10	16
Endosulfan II	. 33213-65-9	0.10	16
4,4'-DDD	72-54-8	0.10	16
Endosulfan sulfate	1031-07-8	0.10	16
4,4'-DDT ·	50-29-3	0.10	16
Hethoxychlor (Hariate)	72-43-5	0.5	· . 80
Endrin ketone	53494-70-5	0.10	16
alpha-Chlordane	5103-71-9	0.5	80
gamma-chlordane	5103-74-2	0.5	80
Toxaphene	8001-35-2	1.0	160
AROCLOR-1016	12674-11-2	0.5	80
AROCLOR-1221	11104-28-2	0.5	80
AROCLOR-1232	11141-16-5	0.5	80
AROCLOR-1242	53469-21-9	0.5	80
AROCLOR-1248	12672-29-6	0.5	80
AROCLOR-1254	11097-69-1	1.0	160
AROCLOR-1260	11096-82-5	1.0	160

Table A (Cont.)

# CONTRACT LABORATORY PROGRAM TARGET ANALYTE LIST INORGANIC DETECTION LIMITS

Compound	Procedure	Vater (ug/L)	Soil Sediment Sludge (mg/kg)
aluminum	ICP	200	40
antimony	furnace	60	2.4
arsenic	furnace	10	2
barium	ICP	· 200	40
beryllium	ICP	5	1
cadmium	ICP	5	1
calcium	ICP	5,000	1,000
chromium	ICP	10	2
cobalt	ICP	50	10
copper	ICP	25	5
iron	ICP	100	20
lead	furnace	3	1
magnesium	ICP	5,000	1,000
manganese	ICP	15	3
mercury	<ul> <li>cold vapor</li> </ul>	0.2	0.008
nickel	ICP	40	8
potassium	ICP	5,000	1,000
selenium	furnace	5	1
silver	ICP	10	2
sodium	ICP	5,000	1,000
thallium	furnace	10	2
tin	ICP	40	8
vanadium	ICP	50	10 • •
zinc	ICP	20	4
cyanide	color	10	2

### . LOG OF BORING NO. 1

## PROPOSED ADDITIONS, FRUEHAUF CORP. PLANT, AVON LAKE, OHIO

BORING LOCATION: As Shown on Boring Location Plan DATESTARTED: 12-11-72

1 " - = 7 - -

SURFACE ELEVATION: Not Taken

DATE COMPLETED: 12-11-72

STRATUM Dep th	DESCRIPTION OF	MATERIAL	SAMPLE NO S TYPE	BANPLE DEPTH	BLOWEFER S'ON SAMPLER	"N' BLOWS
0.0'	Topsoil					
_	Stiff Brown and Gray some Sand, trace of ( of Organic Material	Gravel, trace Moist	14	1.0- 2.5	5-6-8	14
5.0'	(Becomes Very Stiff a	ir 3,5")	24	3.5- 5.01	4-8-12	20
8.5	Very Stiff Gray and E some Clay, trace of S Gravel - Damp	Prown Silt, Sand, trace of	34	6.0- 7.5'	7-7-16	23
10 0'	Soft Gray Weathered S	hale	4.4	8.5-10.0'	10-22-30	72
_						
ا فنقنا			5A	14.0-15.0	63-75/-	133-
_	Bottom of Boring at 1	5.0'	į			
	·					1
				1		
				ì		
-						
	) }			}		
METHOD	Hollow Auger	WATER COSERV			TYPE SAMPLER	
TECHNICIA	N BH-JC	INITIAL PEPTH NOT		_   <u>x</u>	A 3PUIT 5	CCN
JOB NO.:	87663	DEPTH AFTER 24		!	B. C. BHELSY	TUBE

### LOG OF BORING NO. 1A

## PROPOSED ADDITIONS, FRUEHAUT CORP. PLANT, AVON LAKE, OHIO

BORING LOCATION As Shown on Boring Location Plan DATE STARTED: 12-11-72

SURFACE ELEVATION Not Taken

DATE COMPLETED: 12-11-72

STRATUM Depth	DESCRIPTION OF A	PATERIAL	SAMPLE NO & TYPE	BAMPLE DEPTH	BLOWS PER 6" ON SAMPLER	THE DWS
0.0'	(Fill) Bend, Gravel a	nd Cinders				
	(Original) Very Stiff Gray Clay, some Silt, trace of Gravel - Dam	some Sand,	14	1.0- 2.5'	6-10-16	26
5.C' 6.0'	l de la Graver - Da.		2.A	3.5- 5.0'	7-10-17	27
	Very Stiff Brown and Clay, some Sand, trac Moist		3 <b>A</b>	6.0- 7.5'	3-7-11	18
16.6'	(Becomes Hard at 8.5)	>	4.4	8.5-10.01	11-18-22	40
12.0	Soft Gray Shale		4 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1			
المنظنة ا		5.61	5A	14.5-15.0'	100	100+
	Bottom of Boring &t 1	3.0				
-	! !					
	[ ; [					
-	! ! !					
	i 					
	; ;					
MITHOR	Hollow Auget	WATER DEEPRO	TIONS		<b>TURE PARIS.</b> 22	
	no. 100 Auget	INITIAL DEPTH NO	ne	\ _x_	TYPE SAMPLER  A SPLIT SP	00,
CH 16%	<b>E</b> 7 665	DEPTH AFTER			C, \$481.24	TUBE

### LOG OF BORING NO. 2

PROPOSED ADDITIONS, FRUEHAUF CORP. PLANT, AVON LAKE, OHIO

BORING LOCATION As Shown on Boring Location Plan DATE STARTED: 12-11-72

SURFACE ELEVATION: Not Taken

EW-JC

87665

**JOE** NO

DATE COMPLETED: 12-11-72

Depth	DESCRIPTION OF MATER	SAMPLE NO 5 TYPE	BAMPLE DEPTH	BLOWS PER 6" ON SAMPLER	FT OR
0.0'	(Fill) Sand, Gravel and C	inders			
í	(Original) Hard Brown Cla 5ilt, some Sand, trace of trace of Rock Fragments,	Gravel,	1.0- 2.5	9-16-20	36
5.0' -	Organic Material - Moist (Becomes Very Stiff at 3.	5') 2A	3.5- 5.0'	5-6-14	20
r		3.4	6.0- 7.5'	6-11-18	29
'مـف	1	4.4	8.5-10.01	7-12-16	28
- 11.5' .	Soft Gray Weethered Shale				i
<u>.</u> -	: !	5.4	13.5-15.0	18-24-50	74
<u> </u>	Bottom of Boring at 15.0'				<u> </u>
<b>+</b> -	1				
 L _	1 !				
	1 1 1				
	t 				
- -	: i				
- -	t ! !				
	İ				i

COMPLETION DEPTH ROTE

LOG OF BORING NO. 3

## PROPOSED ADDITIONS, FRUEHAUF CORP. PLANT, AVON LAKE, OHIO

BORING LOCATION. As Shown on Boring Location Plan

DATE STARTED: 12-12-72

SURFACE ELEVATION: Not Taken

37 553

DATE COMPLETED: 12-12-72

SHELZY TUBE

D.0' Topacil D.3' Brown and Gray Clay, some Bilt, some Sand, trace of Gravel - Damp    A	STRATUM Depth	DESCRIPTION OF MATERIAL	SAMPLE NO. 8 TYPE	BAMPLE DEPTH	BLOWS PER 6" ON BAMPLER	"N" BLOV
Brown and Gray Clay, some Silt, some   Sand, trace of Gravel - Damp   Sand, trace of Gravel - Damp   Sand, trace of Gravel - Damp   Sand - Stiff Gray Clay and Silt, trace   Sand - Moist   Sand - Moist   Sand - Moist   Sand - Moist   Sand - Sand	0.0'	Topacil			·	
of Sand - Moist  2A 6.0- 7.5' 6-6-12  3A 8.5-10.0' 3-7-11  4A 13.5-15.0' 4-6-12  5oft Gray Weathered Shale  5A 18.5-19.0' 100/3"	-	Brown and Gray Clay, some Bilt, som Sand, trace of Gravel - Damp	e lA	1.0- 2.5'	6-16-24	40
2A 6.0-7.5' 6-6-12  3A 8.5-10.0' 3-7-11  4A 13.5-15.0' 4-6-12  5A 18.5-19.0' 100/3"  6A 24.5-25.0' 100/3"	3,8.51	Very Stiff Gray Clay and Silt, trac	2 1C	4.0- 6.0'		19"
3.0' 16.0' Soft Gray Weathered Shale  5A 18.5-19.0' 100/3"  6A 24.5-25.0' 100/3"	<b>-</b>	of Sand - Moist	2.4	6.0- 7.5'	6-6-12	13
Soft Gray Weathered Shale	.0.0'	; ;	3.4	8.5-10.0'	3-7-11	18
Soft Gray Weathered Shale  5A 18.5-19.0' 100/3"  75.0' 6A 24.5-25.0' 100/3"		· · · · · · · · · · · · · · · · · · ·	4.4	13.5-15.0'	4-6-12	18
	-	Soft Gray Weathered Shale	5A	18.5-19.0'	100/3"	100+
Bottom of Boring at 25.0'	- - - 25.0'	; ! :	6.4	24.5-25.01	100/3"	100-
<del></del> ,		Bottom of Boring at 25.0'				
METHOD Hollow Auger WATER OBSERVATIONS TYPE SAMPLER:	METHOD				TYPE SAMPLER	

## LOG OF BORING NO. 3A

## PROPOSED ADDITIONS, FRUEHAUF CORP. PLANT, AVON LAKE, OHIO

BORING LOCATION. As Shown on Boring Location Plan DATE STARTED: 12-11-72

BURFACE ELEVATION: Not Taken

DATE COMPLETED: 12-11-72

Depth	DESCRIPTION OF MATERIAL	BAMPLE NO B TYPE	SAMPLT DEPTH	BLOWS PER NO "B RIJEMAE	"N" BLOWS
0.0'	Topsoil				
•· •·	Hard Brown and Gray Clay, some Silt, some Sand, trace of Gravel, with Rock Fragments - Damp	13	1.0- 2.5	12-13-30	48
5.0' 3.5'		24	3.5- 5.0'	13-27-50	77
	Very Stiff Gray Clay, some Silt, trace of Sand - Moist	3.4	6.0- 7.51	9-10-13	23
2.0'		4A	8.5-10.0'	6-10-14	24
. ي	Bottom of Boring at 10.0'				\ \ \
<del></del>	•				
·					
ļ					
İ	  -	1			
<del></del>					
•					
	] - !				

METHOD Hollow Auger	WATER CESERVATIONS	TYPE SAMPLER
TECHNICIAN: BH-JC	INITIAL DEPTHHORE	A. SPLIT SPOOM
THE THE THE THE THE THE THE THE THE THE	COMPLETION DEPTH HODE	<b></b>
эсв но - 87665	DIPTH ASTER 24 HAS MODE	E. SHELDY TUSE

## Professional Service Industries, Inc.

#### RECORD OF SUBSURFACE EXPLORATION

\_\_\_\_\_ Date of Boring May 3, 1988 Project Name \_\_Giffels Associates -Sate Ford Motor Company, Ohio Truck Plant Project No.: 142-85054 DEPTH SAMPLE REMARKS DESCRIPTION Q, Black Topsoil, Sand & Gravel, Brn. Silty Clay, Trace Rock Frags., -Moist, V/Stiff. (CL) 255 9-10 3.75 ▼ Encounter @ 7.3' -Gray Silty Clay, Some Shale Frags., Trace Sand, Moist, Stiff. (CL) 10 355 6-8 1.75 End of Boring - 10.0' Completion 7 Dry

## Professional Service Industries, Inc.

## RECORD OF SUBSURFACE EXPLORATION

Boring B-29

Project Name: Giffels Associates Date of Boring May 3, 1988

Site Ford Motor Company, Ohio Truck Plant Project No.: 142-85054

	T	r	<del>,</del>	1	1	Τ	
DESCRIPTION	DEPTH	SAMPLE	N	Qu	Q <sub>p</sub>	R <sub>c</sub>	REMARKS
10.0" Asphalt SURFACE Gravel, Fill	ļ	<del> </del>	{	1	1		-
C-ay Silty Clay, Trace Rock Frags.,	1 -	1AU		ļ			Dry -
F ist, Stiff. (CL)	-				]		-
	_			i		Ì	-
	5 🗷	255	3-4		1.0		
	) -						
					ľ		_
	-				1		_
-G ay Silty Clay, Trace Shale, Frags., Trace Sand, Moist, Stiff. (CL) End of Boring - 10.0'	-	200			l :		-
Frd of Roring = 10 0'	10 =	355	7-7		1.75		=
- End of Bolling - 10.0	-				İ		-
-	-						=
- <b>d</b>							J
_							
-	]						]
_	4				[ [		_
-	-	1				ł	_
	4						-
• •							5
-	i	1					1
	]				]	ł	J
-	4						
	_	[					=
- 4	- 4			i			4
-	4	ļ				İ	-
•	4					ĺ	4
							]
-	7	-		,	į	1	7
	]			j	1		]
	4				į		4
	4		j		İ		4
1	=						=
· _	4	1		Ī			4
• -	7		1	1	1	Ì	j
	J	ł	İ		1	1	]
		- 1		į		1	
	]			1		1	4
	4		İ	j	ł		4
	$\dashv$	]	1				4
	4		Ì				4
	=						4
	╡		1				1

# Professional Service Industries, Inc.

## RECORD OF SUBSURFACE EXPLORATION

Boring	В-:	30	<del></del>		-:	C ' ·	.5 =
Project Name: Giffels Associates			{	Date of	Boring: _	May	3, 1988
Site Ford Motor Company, Ohio Truck P							
DESCRIPTION	DEPTH	SAL E	н	o <sub>u</sub>	Qp	Mc	REMARKS
Brn. Silty Clay W/Sand, Trace Gravel Trace Cinders, Moist, Stiff to V/ Stiff. Fill. (CL)	-	155			1.0-2.25	•	No Water Encounte
Brn. & Gray Silty Clay, Trace Rock Frags., Moist, Hard. (CL)	5 =	25\$	13-19		4.5+		
End of Boring - 10.0'	10 =	355	20-24		4.5		
- - -	=						
	- - -						
· ·	-						
	-						
	1-1-1						
	+						

### Professional Service Industries, Inc.

### RECORD OF SUBSURFACE EXPLORATION

Boring B-31

Project Name Ohio Truck Plant, Ford Mo	otor Co	<u>mpany</u>					
Avon Lake, Chio			F	roject h	No	142-85	5054
DESCRIPTION	DEPTH	SAMPLE	N	٥٠	ap	Мc	REMARKS
SURFACE		1				1	
Stown Silty Clay, Few Seams of Gray	-	155	3-3				No Water
Silty Clay, Some Sand, Few Shale	-						Encountered
rags., Moist, V/Stiff. (CL)		288	4-6		ļ		
•	5 =						
	-		]				
	-						
	-	i	İ		ĺ		
	10 =		į				
			İ			}	
	1 -	•••	50/6"				
_	-	2.5	50/1"				
eachered Gray Shale	15 =						
	-		50/1"				
	1 7	ļ	1				
		احققم	50/1"				
	20 =		j				
•			1				Water @
	-			1		].	₹ 22.0'
		l		İ			3/1/89
Tav Shale	1 25 7	1	1	İ			
rav Shale	25 =	1	- 1			•	
	]			ļ			•
		1		1			
	-	Ì		ł		}	
	30 🖷	İ		1	ł	1	
	-						
	<u> </u>	795	50/1"		- {	1	
<b>.</b>	35						
ore Data: Recovery: 93%	-	_			ĺ	1	
Longest Piece: 4.0"	-	8NX					
e R.Q.D.; 1% ray Shale	-					}	
					ļ		
End of Boring - 40.0'	40				1		
-		1			{	1	
1		-					
_	-				1		
		1			1		
	4	1		Į.	1	İ	

### Professional Service Industries, Inc.

### RECORD OF SUBSURFACE EXPLORATION

Boring \_\_\_\_\_ 8-36 \_\_\_\_ TE 609.0 ±

Segon L. Ascon Nobel (1942)					Property 141-85054			
OESCRIPTION	DEPTH	' <u>5</u> 10-	_ <del></del>	5.		<b>W</b> ,	REMARES	
Asia Asia Asia Asia Asia Asia Asia Asia		<del>-</del>		i	!	<del>*</del> i ;		
Brown Siley Clay & Many Gray Siley	1		-			; ;	 	
Hay Lavers, Few Seams of Brown		1.55	_   -   3_::	1	2.0	1	i de Complet La gi5'	
Clayes Sand, M.ist To Wet, V.Stiff. CDN	<				1	! !	. 4	
		ी विकट्ट	] 	!	2.75		i	
	_					 	<u> </u>	
End of Boring - 8.5'		<del></del>	1 25, 5		<u> </u>		1	
<del>-</del>	10	<b>=</b>		<u>.</u>			[	
Elack Shale.		7						
te: Arver & Split-Spoon Setusal		<del>-</del> :		Í :		'		
g e.51 Of Raceyers		=			;			
						i	i	
		1						
	,	 : 	, ,		i ;			
	-	-				ļ		
	-	_						
		 				i		
	•	i 1				İ		
	-	1-			1	<u> </u>		
	-	<u>.</u>						
	-	Ì				ļ		
	-	₹						
		-			: ;	:		
	-	1				•		
	-		;					
	-	7				! !		
·	· -	•				j		
					i 			
	-	• :						
	-	•				!		
		•				ļ		
				ļ		ĺ		

APPENDIX F

ON-SITE SOIL BORING LOGS

### APPENDIX G

WELL LOGS OF THE AREA OF THE SITE

ORIGINA

PLEASE USE PENCIL OR TYPEWRITER DO NOT USE INK.

State of Ohio DEPARTMENT OF NATURAL RESOURCES Division of Water 1562 W. First Avenue Columbus, Ohio 43212

non-responsive

SHEFFIELD

CONSTRUCTION	DETAILS		BAILING OR PUMPING TEST		
asing diameter 5 6 Leng	gth of casin	g 23	Pumping Rate		
'ype of screenLen			Drawdownft. Date		
'ype of pump	,		Static level-depth to water		
apacity of pump	***		Quality (clear, cloudy, taste, odor)		
epth of pump setting					
Date of completion			Pump installed by		
WELL LO	G*		SKETCH SHOWING LOCATION		
Formations Sandstone, shale, limestone, gravel and clay	From	То	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.		
YELLOW CLAX	0 Feet	15 Ft.	N.		
BLACK SHALE	15-	57	non-responsive		
GREY SHALE	57	6.2			
DRY HOLE					
SMALL AMOUNT	OFGA	S AT 57	1		
WELL PULLED	y FIL	ED	V		
			S. See reverse side for instructions		
Drilling Firm BERN S	CHUS	TER	Date 11-15-65		
Address ELYRIA	·-	•	Signed B Schuser		

### WF'L LOG AND DRILLING REPORT

State of Ohio DEPARTMENT OF NATURAL RESOURCES

Division of Water 1500 Dublin Road Columbus, Ohio

non-responsive

.Section of Township......

CONSTRUCTION DE	TAILS	BAILING OR PUMPING TEST
		Pumping rate G.P. Duration of testhrs
		Developed capacity
Capacity of pump	•	Static level—depth to waterft
Depth of pump setting  Date of completion 4-24-	5-8	Pump installed by
WELL LOG		SKETCH SHOWING LOCATION
Formations Sandstone, shale, limestone, gravel and clay	From To	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.
Share cho constant of the season of the seas	25 90	non-responsive

### WI'L LOG AND DRILLING REPORT

State of Ohio
DEPARTMENT OF NATURAL RESOURCES
Division of Water
1500 Dublin Road

Columbus, Ohio

non-responsive

County Lorans

Township Sheffreld

.....Section of Township.....

## non-responsive

CONSTRUCTION I	DETAILS		BAILING OR PUMPING TEST
,		Pumping rate / Ø G.P.M. Duration of test hr	
			Drawdown ft. Date
			Developed capacity
			Static level—depth to water
Depth of pump setting			Pump installed by
Date of completion			
WELL LO	G		SKETCH SHOWING LOCATION
Formations  Sandstone, shale, limestone, gravel and clay	From	То	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.
	e esta de la companya	2 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	non-responsive
Drilling Firm Died	essel +	Lan	Date 3-7-57

Signed Jun Diederich

PLEASE USE PENCIL OR TYPEWRITER. DO NOT USE INK.

State of Ohio
DEPARTMENT OF NATURAL RESOURCES
Division of Water
1562 W. First Avenue
Columbus, Ohio

non-responsive

County LORAIN

Township AVON

Section of Township.

CONSTRUCTION	DETAILS	:	BAILING OR PUMPING TEST
Casing diameter 554 Leng	th of casin	g PULLET	Pumping rateG.P.M. Duration of testhr
			Drawdown 50 ft. Date
			Developed capacity 16 PM SULPHIER
Capacity of pump	•••••	•	Static level-depth to waterf
Depth of pump setting	•••••	·	Pump installed by
Date of completion	0-19-	59	
WELL LO	G ,		SKETCH SHOWING LOCATION
Formations Sandstone, shale, limestone, gravel and clay	From ···	ob To	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.
CLAY	0 Feet ・ フ	7Ft.	non-responsive
SHALEDARK	24 / Oğum	1	
11 61647 	5/8- 	5-0	
WATER AT 2009  Office between 60 to 10  WATER SULPA	alsa ai said		
2/1		·	
. !	. 464,644		
הווערה	1.9		
· 以1 6.0 8.3	20		See reverse side for instructions
Drilling Firm BERN		STER	Date 10-19-59
Address	A O		Signed B. Seleccole A

W5

# State of Ohio DEPARTMENT OF NATURAL RESOURCES Division of Water Columbus, Ohio

non-responsive

Lason

Section of Township

<u> </u>			
CONSTRUCTION D	ETAILS		With the Art on PUMPING TEST
Casing diameter 5 % Length	h of casing.		Pumping rate G.P.M. Duration of test h
Type of pump 5 /5 well	142	23	Developed capacity
Capacity of pump			Static level—depth to water
Depth of pump setting			Pump installed by
WELL LOG		· **;··· · ; ·	SKETCH SHOWING LOCATION
Formations Sandstone, shale, limestone, gravel and clay	From	То	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.
well#1  Clay : 1 :	1.1.4. s	70	non-responsive
Of cry Shall	m/-4	60	I I
PRAD RESOURCES Vater	OF MAT ivision of Columbur,	TARMON.	
7.Mdid	' /		See reverse side for instructions
Drilling Firm med	entot	som	Date 8-20-5-1
Address 910 Redgeurs	lle	***************	Signed Tru Gredeinh

W6

ORIGINAL

PLEASE USE PENCIL OR TYPEWRITER DO NOT USE INK.

State of Ohio DEPARTMENT OF NATURAL RESOURCES Division of Water 1562 W. First Avenue Columbus, Ohio 43212

non-responsive

County LORAIN Township AVON

.....Section of Township.....

<del></del>	<del></del>	<del></del>			
CONSTRUCTION	DETAILS		BAILING OR PUMPING TEST		
Casing diameter 558 Leng	th of casin	g 23	Pumping Rate 10 T.G.P.M. Duration of test 15 hr		
Type of screen Leng	th of scree	n	Drawdownft. Date		
Type of pump	***************************************		Static level-depth to waterf		
Capacity of pump			Quality (clear, cloudy, taste, odor)		
Depth of pump setting			TRACE OF GAS		
Date of completion			Pump installed by OWNER		
WELL LO	G*		SKETCH SHOWING LOCATION		
Formations Sandstone, shale, limestone, gravel and clay	From	то	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.		
YELLOW OLLY	0 Feet	9 Ft.	non-responsive		
RLUE CLYYASING	9	15			
SAND	15	17			
DARK SHHE	62	50			
***************************************			-		
WATER	421				
CAS WITH		-12			
		<u> </u>			
******		<del></del>			
4	·				
		<u> </u>	See reverse side for instructions		
Drilling Firm BERN	SCHU	STER	Date 4-29-68		
Address ELYRIA	8	************	Signed B Selicesto		
-			·		

\*If additional space is needed to complete well log, use next consecutive numbered form.

### WEI LOG AND DRILLING REPORT

W7 ORIGINA

PLEASE USE PENCIL OF TYPEWRITER DO NOT USE INK.

State of Ohio DEPARTMENT OF NATURAL RESOURCES Division of Water 1562 W. First Avenue Columbus 12, Ohio

non-responsive

County LORAIN Township AVON LAKE Section of Township

CONSTRUCTION DETAILS

Address ELYRIA

BAILING OR PUMPING TEST

CONSTRUCTION	DEINIES		DAILING OR FOMPING 1EST
Casing diameter 5 5g. Leng	gth of casing	g	Pumping Rate G.P.M. Duration of test hrs
Type of screenLeng	gth of screes	n	Drawdown 6 0 ft. Date
Type of pump		•••••	Static level-depth to waterft
Capacity of pump			Quality (clear, cloudy, taste, odor)
Depth of pump setting			CLEHPING
Date of completion			Pump installed by
WELL LO	G		SKETCH SHOWING LOCATION
Formations Sandstone, shale, limestone, gravel and clay	From	То	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.
CLAY	0 Feet	Ft.	
SHALE LIGHT	10 15501 :	14	non-responsive
DARK SHALE	14	61	
Marchine 23 Sales	3 1(30)		
WATER APPO	X 39 This pail That is gr	o et o e cello. Costo de cello	
$\mathfrak{g}_{1} \simeq \mathfrak{t}_{1}^{2} \otimes_{\mathbb{R}^{2}} \mathfrak{g}_$	the day to de	1	
<i>4.</i>	10 14 10 10		
un unitat i	17 y 17 2, 2 - 14 -	2.50	
	7 1, .:5	I.	
	Contain.		
	:		
E Carry			
			See reverse side for instructions
	<u> </u>	<u>L</u>	
Drilling Firm BERN	SCHUS	TER	Date 7-14-69

non-responsive

AND DRILLING REPORT

T OF NATURAL RESOURCES Division of Water Columbus, Ohio

non-responsive

County 201am Township

Section of Township or Lot Number Leven

## non-responsive

CONSTRUCTION D	ETAILS	PUMPING TEST		
Casing diameter 5.78Lengt	h of casing	Pumping rateG.P.M. Duration of test		
Type of screenLengt	h of screen		Drawdownft. Date	
Type of pump			Developed capacity	
Capacity of pump			Static level-depth to water	
Depth of pump setting	•••••	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
WELL LOC	}	SKETCH SHOWING LOCATION		
Formations Sandstone, shale, limestone, gravel and clay	From	) : <b>To</b> ;	Locate in reference to numbered State Highways, St. Intersections, County roads,	
Clary Black Shalo	j	Ft. Grant and State of State o	non-responsive	
mates in Shall	in in in in a declar of the interest of the in	man grade Valle man sa Valle ad la da ca lacido me		
	on in gration of	• • • • • • • • • • • • • • • • • • •		
The second secon	gradien tu	日本 おこ		
121,410 <b>4</b> , 14 14	22.	. / : : : : . 1		
	aion of Wi			
	iumtus, O:	Э		
			See reverse side for instructions	

Address No Ridgeville O

Signed In brickerids

### WELL LOG AND DRILLING PEPORT

State of Ohio

DEPARTMENT OF NATURAL RESOURCES
Division of Water

1562 W. First Avenue Columbus, Ohio 43212

OR TYPEWRITER
DO NOT USE INK.

non-responsive

ORIGIN

County LDRAIN

Township AVUN

.....Section of Township.....

## non-responsive

CONSTRUCTION	DETAILS		BAILING OR PUMPING TEST
Casing diameter 5 5 Leng	gth of casing	Pumping Rate	
Type of screenLeng	gth of screen	Drawdownft, Date	
Type of pump SUB		, o o tam o o a <sub>rea</sub> a pro o m <del>o departmin</del> e.	Static level-depth to water
Capacity of pump			Quality (clear, cloudy, taste, odor)
Depth of pump setting	<u>' 5 '                                 </u>		NA NOOR CEARING
Date of completion	-16-6	62	Pump installed by PUMP LOWERED 42
WELL LO	G*	-	SKETCH SHOWING LOCATION
Formations Sandstone, shale, limestone, gravel and clay	From	То	Locate in reference to numbered State Highways, St. Intersections, County roads, etc.
	0 Feet	Ft.	N.
WELL DRAILED FOR MORE RE LIGHT SHALE RED "  VV ATER IN S APPOX 20' 4" S'INER Y  NO WATER	5 E RV E 40 45 70 IV E 3 F 1	- 45 - 100 - M	w.
P /	ا ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ ـ		See reverse side for instructions
Drilling Firm BERN	3 C HUS	TER	Date $\frac{7-19-66}{2}$
Address <u>LyR</u> 1	A		Signed Believe

\*If additional space is needed to complete well log, use next consecutive numbered form

## NON-IESPONSIVE L LOG AND DRILLING REPORT

W10 ORIGIN

State of Ohio
RTMENT OF NATURAL RESOURCES
Division of Water
Columbus, Ohio

non-responsive

Selvati

County 2 ON A 1 10 Township AVO

Section of Township ....or Lot Number.....

CONSTRUCTION D	ETAILS	PUMPING TEST		
Casing diameterLengt  Type of screenLengt  Type of pump	h of screen	Pumping rate		
Capacity of pump			Static level—depth to water	
Depth of pump setting		Pump installed by		
WELL LOG	·	SKETCH SHOWING LOCATION		
Formations Sandstone, shale, limestone, gravel and clay	From	То	Locate in reference to numbered State Highways, St. Intersections, County roads, et	
BLACK TO HAZE STORY WAS A STORY OF THE SERVICE	tiring ap.  Leviling of no.  Leviling of no.  Leviling of no.	engi ewab bat mgan as as as coa mn cast as co	5.1 5.1 5.1	

NON-responsive L Log and Drilling REPORT

HO WATER RESOURCES BOARD Department of Public Works 53 E. Broad St., Columbus 15, Ohio

non-responsive

Section of Township or Lot Number.....

Construction details  Casing diameter 5 2 Length of casing 6  Type of screen NONE Length of screen 7  Type of pump 6  Capacity of pump 9  Depth of pump setting 6  WELL LOG			PUMPING TEST  Pumping rate				
				Formations Sandstone, shale, limestone, gravel and clay	From	То	Locate in reference to numbered State Highways, St. Intersections, County roads, et
				RCF4 DOARD	es an coorda ce in relation 2.2 A.M. st state hig.	En received to the control of the co	Double Committee
						-	

Address £LYRIA O